2703U

UNIVERSAL DOOR-ENTRY PHONE WITH 2 BUTTONS. MINI SERIES

MINI series universal door-entry phone, compatible with most of the door-entry phones produced by leading international manufacturers. Ideal in door-entry phone system replacements and repairs. Key button and additional button for extra services with independent common. Electronic ringtone. Call volume and privacy adjustment by means of 3-position selector. Privacy function activation is indicated by a red light. Also features loudspeaker volume control and microphone volume control to meet all possible requirements, can be used in systems with positive common or systems with negative common. Dimensions: 4.06"x7.48"x1.18".

2703U

UNIVERSAL DOOR-ENTRY PHONE WITH 2 BUTTONS. MINI SERIES

MAIN SPECIFICATIONS

Audio system:	Yes
Audio/video system:	No
Flush-mounted:	No
Wall-mounted:	Yes
Desk base-mounted:	Yes
Hands-free function:	No
Induction loop function:	No
Product colour:	White
Sensitive Touch technology:	No
Total buttons:	2

FUNCTIONS

Actuator control function:	Yes
Privacy function:	Yes
Electronic bell:	Yes
Key button function:	Yes

HARDWARE SPECIFICATIONS

Type of finish:	Plastic

SETTINGS

Loudspeaker volume control:	Yes
Microphone volume control:	Yes
Ringtone volume control:	Yes

GENERAL DATA

Product height (inches):	7.48
Product width (inches):	4.06
Product depth (inches):	1.18

COMPATIBILITY

Traditional system:	Yes

TECHNICAL SPECIFICATIONS

IP Rating:	IP30
Operating temperature (°F):	32 ÷

The technical specifications are subject to variations without warning.

2703U

UNIVERSAL DOOR-ENTRY PHONE WITH 2 BUTTONS. MINI SERIES

TECHNICAL SPECIFICATIONS	
Product weight (oz):	0.57
Clamps:	A B C D E C2 P2

The technical specifications are subject to variations without warning.

Comelit
Passion.Technology.Design.

2703U

UNIVERSAL DOOR-ENTRY PHONE WITH 2 BUTTONS. MINI SERIES

ACCESSORIES

2708W

DOOR-ENTRY PHONE W/ 2 BTNS FOR SIMPLEBUS AUDIO. MINI SER.
MINI series door-entry phone for Simplebus system with electronic call, key button and additional button for extra services (switchboard call, actuator, generic uses). Call volume and privacy adjustment by means of 3-position selector. Privacy activation is indicated by a red light. Allows floor door call management. Complete with 8-position dip-switch for selection of the desired user code. Dimensions: 105x191x28 mm

2712W

Entry phone for kit. Mini series.
MINI series door-entry phone for kit KAE061 with electronic call, call volume adjustment and privacy function. With one lock release button and one free button (C/N.O.). Allows call repetition. Dimensions: 105x191x28 mm

2719W

DOOR-ENTRY PHONE W/ 5 BTNS FOR SIMPLEBUS TOP A/V. MINI SER.
MINI series door-entry phone for SBTOP system with electronic call, key button and 5 additional buttons for extra services/intercom function. 1 of the 5 buttons can be used as a C/N.O contact. Equipped with a LED that may be used for various signals (busy, doctor function). Complete with 8-position dip switch for selection of the desired user code. Door-entry phone for use in all Simplebus systems. Allows management of floor door call and sending of alarm signals to the porter switchboard. Also allows direct intercom calls between users without the aid of an interface or porter switchboard. Fitted with terminal art. 1214/2C. Dimensions: 105x191x28 mm

2738W

DOOR-ENTRY PHONE W/ 2 BTNS FOR SIMPLEBUS TOP A/V. MINI SER.
MINI series door-entry phone for SBTOP system with electronic call, key button and additional button for extra services (switchboard call, actuator and generic uses). Call volume and privacy adjustment by means of 3-position selector. Privacy activation is indicated by a red light. Allows floor door call management. Complete with 8-position dip-switch for selection of the desired user code. Door-entry phone for use in mixed audio/video SBTOP systems. Fitted with terminal art. 1214/2C. Dimensions: 105x191x28 mm

2742W

DESK BASE FOR MINI DOOR-ENTRY PHONES
Desk base for desktop conversion of MINI series door-entry phones. Complete with 1.5 m cable and connection coupling.

The technical specifications are subject to variations without warning.