# **GSM** Antenna



The Art.434 antenna can be used with any of the VIDEX range of GSM intercom modules:


- GSM4K PRO series (Art.4810).
- GSMVRK series (Art.150).
- Digital GSM (Art.4812, Art.4812R).
- Art.2270 GSM interface.

With its robust and compact design it can be mounted externally and can be used on a 2G, 3G or 4G network.

# **RF & Electrical Specification**

Network Coverage	2G, 3G and 4G networks
Working Frequency	GSM (900MHz), DCS (1800MHz)
Gain	3 ± 5 dBi (avg.)
V.S.W.R. (Voltage Standing Wave Ratio)	< 2.0
Polarization	Linear
Impedance	50 Ohms





## Data, Materials & Dimensions

Cable	RG174 coax cable
Cable Length	3m (approx.)
Connector	SMA male
Materials	Antenna Hat: ABS Antenna Body: ABS & PVC
Colour	Black
Mounting	External use, surface mount
Dimensions (mm)	120 (H) x 30 (base diameter)

#### **VIDEX SECURITY LTD.**

### **Main UK Office**

1 Osprey, Trinity Park, Trinity Way, London, E4 8TD tel: 0370 300 1240 - fax: 020 8523 5825

www.videxuk.com

### **Northern UK Office**

Unit 4-7 Chillingham Ind. Estate, Chapman Street, Newcastle Upon Tyne, NE6 2XX tel: 0370 300 1240 - fax: 0191 224 1559



