

**1415****USER BRANCH UNIT WITH INTEGRATED LINE PROTECTION  
S2**

Part. 1415 is used to branch up to 4 internal units on the riser (with a different address for each output) and also acts as line protection, isolating the branches in the event of power surges or short circuit. This unit can be used with systems with Simplebus 2 video systems, and as it is powered by the 2 wire bus it does not need any additional power supply. Max. 100 users can be connected to each Mixer part. 4888 or part. 4888C whatever the number of Art. 1415 used, and max. 3 internal units can be connected in cascade for each output of Art. 1415.



**1415**

## USER BRANCH UNIT WITH INTEGRATED LINE PROTECTION S2

Input connector	Terminal block
CE certifications	EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

### MAIN FEATURES

Height (mm)	35
Width (mm)	60
Depth (mm)	85
Operating temperature (°C)	-25 ÷ 50
Operating humidity (RH max) (%)	25 ÷ 95
DIN rail mounted	Yes
DIN modules (no.) (n°)	4
Supply voltage	Bus line

### GENERAL DATA

Type of finishing materials	Plastic
Product color	White

### COMPATIBILITY

Simplebus 2 audio/video system	Yes
--------------------------------	-----