



1952N

AUDIO/VIDEO PORTER SWITCHBOARD. VIP



Tabletop audio-video porter switchboard with touch screen and alphanumeric keypad, for the simple and intuitive use of functions. Displays visitor images and the name of the user to call. Day/night mode and user/user intercom service. 12 VDC power supply with art. 43082 or direct from the ViP Ethernet network.



1952N

AUDIO/VIDEO PORTER SWITCHBOARD. VIP

ELECTRICAL CHARACTERISTICS

PoE power supply	Standard IEEE 802.3af, Comelit PoE (56VDC)
Maximum absorption (W)	11
Max/min absorption (mA)	50 ÷ 200

MAIN FUNCTIONS

Self Activation	Yes
-----------------	-----

GENERAL FEATURES

CE certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)
OSD display	Yes
Type of buttons	Mechanical

MAIN FEATURES

Height (mm)	110
Width (mm)	225
Depth (mm)	225
Product weight (g)	1100
Operating temperature (°C)	-5 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 90
Supply voltage	12VDC
Maximum current absorption (mA)	200

SOFTWARE/FIRMWARE SPECIFICATIONS

IP assignment	AUTO IP, DHCP, STATIC
No. of storable users (n°)	4000

GENERAL DATA

Type of finishing materials	ABS
Product color	Black RAL9005



1952N

AUDIO/VIDEO PORTER SWITCHBOARD. VIP

GENERAL DATA

ViP	Yes
Display size (")	3.5
Display type	Graphic LCD
Touch screen	Yes
Number of push-buttons	28
Communication ports	RJ45 (Ethernet)
Loudspeaker volume	Yes
Microphone volume	Yes
Type of LAN network	Ethernet 10 Mbit/s
IP address assignment	DHCP, AUTO IP, static IP
Environmental class	III
Door opener	Yes

FUNCTIONS

Alarm function	Yes
Actuator control function	Yes
Intercom function	Yes
Key button function	Yes

COMPATIBILITY

Vip system	Yes
------------	-----

MOUNTING/INSTALLATION

Desk base-mounted	Yes
-------------------	-----

AUDIO/VIDEO FEATURES

Audio/video system	Yes
--------------------	-----

CONNECTIVITY

Ethernet ports (n°)	1
---------------------	---