LME17E-II & LME19E-II

17" & 19" LED Monitor's

AUDIO IN / OUT
LED
HI RES
COLOUR
OSD
MULTI LANGUAGE
HDMI INPUT
VGA / BNC INPUT
WIDE ANGLE VIEW

The LME17E-II 17" & LME19-II 19" LED Monitors offer excellent picture quality and a sleek and pleasant design normally associated with higher end units. An impressive 1000:1 contrast ratio and 1280 x 1024 resolution and response time of 5ms gives you the ultimate performance and delivers crisp clear images.

This range of monitors also feature HDMI, VGA & BNC input capabilities providing various connection options. The slim design maximises desktop space and makes a perfect fit for almost any office or commercial application. The desk mount can be easily removed to allow the monitor to be fitted with any 75mm VESA accessories.

Key Features

- 1280 (H) x 1024(V) Resolution
- Wide Viewing Angle
- High Contrast Ratio
- Built in Speakers
- HDMI, BNC & VGA
- Multi language OSD
- Slim Design
- Fast Response Rate

V1.01

CBC GROUP
Unit 9 Garrick Road Industrial Estate, Irving Way, London, NW9 6AQ, England
tel: technical support +44 (0)20 8732 3339 +44 (0)20 8732 3355
fax: +44 (0)20 8202 3387 www.cbceurope.com

RoHS 2002/95/EC
CE
ISO 9001 REGISTERED FIRM

LME17E-II & LME19E-II

17" & 19" LED Monitors

Specifications

Description / Model	LME17E-II	LME19E-II
MONITOR SPECIFICATION		
Panel Type	17" (4:3) LED Monitor	19" (4:3) LED Monitor
Case Type	Plastic	
Max Resolution	1280 (H) x1024 (V)	
Pixel Pitch	0.264 (H) x 0.264(V) mm	0.294 (H) x 0.294 (V) mm
Bezel Thickness	Top/Bottom 18mm; Left/Right 15mm	19 mm
Active Display area	337.92(H) x 270.34(V) mm	376.32 (H) × 301.06 (V) mm
Contrast ratio	1000:1	
Brightness	250 cd/m2	
Response time	5ms	
Display Colours	16.7 M	
Video Sychronization	Yes	
PC Compatible Frequence	30-60KHz(H) / 56-75Hz(V) Max	
Viewing Angle	160°/160° (H/V)	
Adjustable Colour Temperature	9300K / 6500K / 5800K / User	
Video Compatability	NTSC/PAL	
Aspect Ratio	4 : 3 Ratio	
VGA Auto Frequency Correction	Yes	
Speaker	2 x 2.5W	
Number of Speakers	2	
Sound Demodulation	Audio, Stereo	
Mute	Yes	
Work Temperature / Humidity	Temperature: -10 to +45°C Humidity: 5%~70%	
Volume +/- Power ON/OFF	Yes	
Video Interface	1xVGA,1x HDMI, 2x BNC Composite In, 2x BNC Composite Out, 1x SVideo, 1x PC Audio, 2x Audio	
Audio Interface	Yes	
Power Interface	AC in x 1	
Termination	75 Ohms	
Safety & EMC Certification	CE, FCC, ROHS, Weee	
Vesa Standard Mount	75mm x 75mm	
Stand Type	Desktop	
Colour	Black	
Button Position	Button Position Right Hand Side/ Back	
Packing Dimension	445 x 445 x 150mm	490x170x500mm
GROSS Weight	4.6 Kg	5.4 Kgs
Power Supply	12VDC 3Amp	
Voltage Power	AC110V~240V 50/60Hz	
Power Consumption	<18W	<20W
OSD Control	Contrast, Brightness, Colour, Tint, Sharpness, Colour Temperature, 3D Interlace, 3D Comb Filter, DNR, PIP, POP	
OSD Language	English, German, Italian, Spanish, French, Russian, Portuguese, Polish	
Accessories	VGA Cable, User Manual, Audio Cable, Power Adapter, Power Lead	

NB. Specification subject to change without notification

V1.01

CBC GROUP

Unit 9 Garrick Road Industrial Estate, Irving Way, London, NW9 6AQ, England
tel: technical support +44 (0)20 8732 3339 +44 (0)20 8732 3355
fax: +44 (0)20 8202 3387 www.cbceurope.com

RoHS 2002/95/EC CE
ISO 9001 REGISTERED FIRM