LMEG32

32" LCD CCTV Monitor, Metal cased & Glass fronted















The C-ML range of commercial LCD Monitors offers excellent picture quality and a sleek and pleasant design normally associated with higher end units. An impressive 1000:1 contrast ratio and 1366 x 768 resolution and response time of 8ms gives you the ultimate performance and delivers crisp clear images.

This range of monitors also feature an analogue input, VGA and S-Video capabilities providing various connection options as well as HDMI input. The slim design maximises desktop space and makes a perfect fit for almost any office or commercial application. The desk mount can be easily removed to allow the monitor to be fitted with any standard 100mm VESA accessories.

Key Features

- POS / ATM Terminals
- Wide viewing angle
- High contrast ratio
- Built in speaker
- Multi language OSD

- 3D comb filter High quality motion adaptive
- 4H comb filter adaptive for the best image quality
- ▶ 3D noise reduction
- 1366(H) x 768(V)) Resolution







LMEG32 32"LCD CCTV Monitor

Specifications

Description / Model	LMEG32
MONITOR SPECIFICATION	
Display Type	32" Active Matrix TFT LCD Module
Resolution	1366(H) x 768(V)
Pixel Pitch	0.50175 (H) x0.501757 (V)
Colors	16.7 million colors
Contrast ratio	1000:1 (Typical)
Brightness	500 Cd/m2
Response time(tr/tf)	5 ms
Display area	697.68mm(H) x 392.25mm(V)
Composite Inputs	(VGA)x1, (S-Video)x1, (PC Audio)x1, (BNC)x2, HDMI
Composite Outputs	(BNC)x2
Speaker	10W x 2
Power consumption	150W in "ON" mode
Wall hanging	Yes
Auto adjustment	Yes
Viewing Angle L/R	70°/80°
Viewing Angle U/D	70°/80°
OSD Control	Contrast, Brightness, Clock, Phase, H-Position, V-Position, Language.
OSD Language	English, Germany, French, Italian, Spanish
Dimensions	760(W) x 450(H) x 45(D) mm
Accessories	Power cord, Adapter, User's guide, Audio cable
Weight	Net :38kg Gross : 43kg
Speaker	Multimedia Speakers
Certificate	Energy Star, FCC-DOC, CE, ROHS
Warranty Period	3 Years



