

## V992D-N4

### Compact Vandal-Resistant Network Dome Camera



- 1080p resolution
- Digital day/night performance
- H.264 high-profile and M-JPEG compression
- 0.63 lux @ 50 IRE
- Power-over-Ethernet (IEEE 802.3af)
- Dual streaming video
- IP66 rated

### Overview

Vicon's V992D-N4 HD IP Dome Camera is designed for demanding security installations. This network camera delivers crisp clear images that satisfy any installation need. The camera provides 1080p resolution.

The V992D-N4 camera provides dual-streaming video and supports H.264 compression technology, drastically reducing file sizes and conserving valuable network bandwidth. Users can receive multiple streams simultaneously in different resolutions, frame rates and image qualities for viewing on different platforms.

Installation of the V992D-N4 is made easy and cost effective with Power over Ethernet (IEEE 802.3af), which eliminates the need for power cables. Additionally, a composite output is provided for installation using a spot monitor (NTSC/PAL selectable). This compact dome fits unobtrusively in any location.

In order to adapt to the low light lighting conditions in challenging indoor environments, like restaurants or train and bust stations, the V992D-N4 provides a digital day/night feature for superior image quality around the clock. For protection against the elements, the camera dome is IP66-rated. The camera includes a fixed 4.0 mm megapixel lens. The camera dome provides 3-axis adjustment for any angle of view.

The camera is ONVIF compliant and can be used with many popular VMS systems, including ViconNet®.

Resolution	Model Number
1080p resolution (2 megapixel)	V992D-N4

### Model Description

<b>Model</b>	<b>V992D-N4</b>
<b>Image Sensor:</b>	1/2.8-inch Sony IMX-036 CMOS sensor
<b>Max Resolution:</b>	1080p
<b>Image Settings:</b>	Adjustable bit rate. Flip and mirror. Configurable brightness, contrast, color, hue, sharpness. White balance. AGC. AES. Automatic or manual day/night mode. BLC (Backlight Compensation). Digital zoom. Motion detection.
<b>Shutter Speed:</b>	1/4, 1/10, 1/12.5, 1/15, 1/20, 1/25, 1/30, 1/50, 1/60, 1/100, 1/120, 1/240, 1/480, 1/960, 1/1024, 1/2000 sec
<b>Electronic Zoom:</b>	2 ~ 10X (client software)
<b>Day/Night Performance:</b>	Digital Day/Night
<b>S/N Ratio:</b>	Greater than 50 dB
<b>Minimum Illumination:</b>	0.06 fc (0.63 lux) @f/3.5, 50 IRE

### Lenses

<b>Lens*:</b>	Fixed, f=4.0 mm; f number: 2.0
<b>Angle of View:</b>	Horizontal: 71.45°; Vertical: 40.20°; Diagonal: 81.98°

### Network Video Transmission

<b>Network:</b>	10Base-T, 100Base-TX, RJ-45
<b>Image Compression:</b>	H.264 (Main Profile); M-JPEG available for 2nd stream
<b>Resolution:</b>	1920x1080, 1280x720, 1280x1024, 1024x768, 704x480/576, 640x480, 352x240/288, 320x240
<b>Protocols:</b>	IPv4, TCP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, IGMP, ICMP, DHCP, DNS, DDNS, UDP, ARP
<b>Frame Rate:</b>	1 ~ 30 fps
<b>Users:</b>	Live viewing for up to 10 clients
<b>Web Browser:</b>	Internet Explorer® 7.0 and above, Firefox®, Chrome®, Smart Phone/PAD@V2.0
<b>Alarms:</b>	VMD Alarm Trigger: 4 ROI, user set, 10 step sensitivity. Alarm Event: Email, FTP, Post Alarm
<b>Security:</b>	Password protection

### Mechanical and Electrical

<b>Construction:</b>	Die-cast aluminum; Torx (T20) screws; polycarbonate dome
<b>Mounting:</b>	Surface mount
<b>Camera Angle of Adjustment:</b>	3-axis adjustment, pan, tilt and roll (azimuth). 360° pan; 90° tilt; 360° rotation
<b>Indicators, Controls and Connectors:</b>	LEDs: status/network. Reset Button: sets factory defaults. PoE/Network: RJ-45 CAT 5. Composite output provided for installation (NTSC/PAL selectable). Focus Adjustment. Control button (for video format).
<b>Dimensions:</b>	Height: 2.65 in. (67.5 mm); Diameter: 4.3 in. (110 mm)
<b>Weight:</b>	0.8 lb (0.36 kg)
<b>Input Power:</b>	PoE (IEEE 802.3af Class 2)
<b>Current:</b>	68 mA @ 48 VDC
<b>Power Consumption:</b>	3.3 W

### Environmental

<b>Operating Conditions:</b>	Temp: 32 to 104° F (0 to 40° C); Humidity: less than 90%, non-condensing
<b>Approvals:</b>	FCC Class A, CE, IP66

\*The V992D dome is also available with a 2.1 mm fixed lens, model V992-N2, and a 6 mm lens, model V992-N6. Ask your Vicon Representative for details.


Data Sheet Number: V248-10-04

Dated: 8/2012

Vicon Data Sheet Number: 8009-7248-10-04

Specifications subject to change without notice.

- ① Control Button
- ② Network LED
- ③ Status LED
- ④ Reset Button



- ⑤ Video output for service monitor
- ⑥ Lock nut
- ⑦ Focus adjustment
- ⑧ Network (RJ-45 PoE required)

Vicon, ViconNet and their logos are registered trademarks of Vicon Industries Inc. Internet Explorer is a registered trademark of Microsoft Corporation; Chrome is a registered trademark of Google; Firefox is a registered trademark of Mozilla Corp. Copyright © 2012 Vicon Industries Inc. All rights reserved.