



WNVR832P5

H.265 32 Channel High Definition PoE NVR

The WNVR832P5 is a H.265 32 Channel High Definition Network Video Recorder. The NVR features 32 Channel Simultaneous Playback as well as 16 PoE Network Ports with IPC Direct Connection to NVR.



WNVR832P5 FRONT



WNVR832P5 BACK

Key Features

- Up to 5MP Real Time Recording across all 32 Channels
- H.265 Video Compression
- Supports 32 IP Stream Input
- Supports up to 16 PoE Power Supply
- 32 Channel Simultaneous Playback
- Supports 4K Output
- 8 HDD Bay (Up to 6TB)
- Multi-Mode Recording: Manual, Sensor (Via the Alarm Inputs of the IP Camera), Schedule and Motion
- Multi-User Online Simultaneously
- Support PTZ Presets
- Pentaplex: Live, Record, Playback, Backup and Remote Operation
- DHCP, DDNS, PPPoE, Network Protocol, IE Browse and CMS Supported
- Support IPC Direct Connection to NVR
- Dual Stream Technology to Encode Recording Stream and Network Stream
- User can adjust Network Stream to fit Bandwidth without changing Recording Quality
- User Friendly Graphic User Interface (GUI), Windows Style, Operation By Mouse
- Apple & Android Mobile Phone Remote Viewing

Technical Specification

Model Number	WNVR832P5
Compression	Standard H.265
OS	Embedded Linux
IP Video Input	32 Channels
Network Access Bandwidth	256 Mbps
Video Output	HDMI: x1: 4K x 2K / 1920 x 1080/1280 x 1024 VGA: 1920 x 1080/ 1280 x 1024
Recording Resolution	5MP/4MP/3MP/1080P/960P/720P
Frame Rate	1~25fps / CH (PAL), 1~30fps / CH (NTSC)
Audio	Output: RCA x1, 2 Way Audio: RCA x1
Record Stream	Dual Stream Recording
Recording Mode	Manual, Timer, Motion, Sensor
Playback	Max 32ch Simultaneous
Search	Time slice/time/event/tag search
Alarm Mode	Time/Calendar Search, Event (Motion, External Alarm)
Function	Play, Pause, FF, FB, Digital Zoom
Network Interface	RJ45 x1 (10/100 Mbps x1)
PoE Port	RJ45 x16
Network Interface	RJ45 x1
Protocol	TCP/IP, UDP, DHCP, DNS, PPPOE, DDNS
Web Client	Up to 10 Users Online
Mobile OS	iPhone, Blackberry, Android, Windows Phone
Mobile Function	Multi-Screen Surveillance (for certain model), Record, Snapshot, PTZ Control, Save the Device list
Ports	RS485: x1 (Support PTZ) USB 2.0: x2 Ports
Remote Controller	Yes
Storage	x8 HDD (Up to 6TB per Bay)
Power Supply	DC48V
Working Environment	10 ~ 55°C, 10% ~ 90% Humidity
Dimensions (W x D x H)	430 x 450 x 90 mm

Genie CCTV reserves the right to change specifications without notice. Please contact your representative to confirm current specifications.

Dimensions (mm)

