

The LMV-215 is a 21.5" HDMI and VGA LED monitor. The monitor has a fast response time of 5ms so no image ghosting and is also able to continually work for 24/7. The monitor features built-in speakers and a detachable stand and is able to fit VESA mount options.

Key Features

- Full HD 1920 x 1080
- 5ms fast response time
- 3D digital noise reduction
- HDMI / VGA
- 16:9 grade A panel
- Supports 24/7 continuous
- Desk stand (Detachable)
- Built-in speaker
- Standard and VESA mount options



LMV-215

Accessories



BT7510/B
Fixed LCD / TFT Wall
Mount Bracket



BT7511/B
Tilttable LCD / TFT
Wall Mount Bracket



BT7518/B
Tilt & Swivel Wall
Mount Bracket



BT7512/B
Single Arm Tilt & Swivel
Wall Mount Bracket



BT7513/B
Double Arm Wall
Mount Bracket

Specification

Model Number	LMV-215
Panel Type	LED
Case Type	Plastic
Maximum Resolution	1920 (H) x 1080 (V)
MTBF	30,000 hrs
Active Display Area	476.64 x 268.11 (HxV)
Pixel Pitch	0.24825 x 0.24825 (HxV) mm
Bezel Thickness	Left / Right 16mm, Top 17mm, Bottom 21mm
Contrast Ratio	1000 : 1
Brightness	250 cd / m ²
Response Time	5m.sec (G to G)
Viewing Angle	89/89/89/89 (Typ.) (CR-10)
Display Colours	16.7m
Video Synchronisation	Yes
PC Compatibility	Yes
Aspect Ratio	16:9
VGA Auto Frequency Correction	Yes
Speakers	2
Sound Demodulation	Yes
Mute	Yes
Work Humidity	5% - 90%
Work Temperature	-10 to +50 °C
Volume +/- Power On/Off	Yes
Video Interface	HDMI, VGA
Audio Interface	1 x Input
Termination	N/A
Certification	CE, ROHS, FCC
VESA	100mm x 100mm
Stand Type	Table stand
Colour	Black
Button Position	Back , Bottom right
OSD	Contrast, Brightness, Saturation, Hue
OSD Language	English, Italian, German, French, Russian, Spanish, Portuguese, Polish, Danish, Dutch
Power Supply	DC12V
Power Consumption	21 Watt
Power Interface	DC 2.1mm
Dimensions	508 (W) x 305.9 (H) x 16.8 (D) mm
Weight	

Bioaccess Sales Ltd. reserves the right to change specifications without notice. Please contact your representative to confirm current specifications.