

OPA2ED-MF 2MP HD IR Vandal Dome

KEY FEATURES

- 2 megapixel True Day Night
- IP67 - Internal and external installations
- Integrated IR illumination - low light conditions
- Fixed lens - wide angle
- Quad video format - CVI/TVI/AHD/CVBS



Features		OPA2ED-MF Feature Specification
Camera	Image Sensor	1/2.7" CMOS
	Effective Pixels	1920(H)×1080(V)
	Electronic Shutter Speed	PAL: 1/25-1/100000 NTSC: 1/30-1/100000s
	Minimum Illumination	0.04Lux/F1.85, 30IRE, 0Lux IR on
	IR Distance	Up to 30m (98feet)
Lens	Focal Length	2.7-12mm
	Max. Aperture	F1.8
	Angle of View	H: 106°-33° V: 56°-19°
	Focus Control	Manual
Video	Resolution	1080P (1920×1080)
	Frame Rate	25/30fps@1080P, 60fps@720P
	BLC Mode	BLC / HLC / DWDR
Certifications	Certifications	CE (EN55032, EN55024, EN50130-4)
Electrical	Power Supply	12V DC ±30%
	Power Consumption	Max 4.6W (12V DC, IR on)
Environmental	Operating Conditions	-40°C - +60°C (-40°F - +140°F)
	Storage Conditions	-40°C - +60°C (-40°F - +140°F)
	Ingress Protection	IP67
	Vandal Resistant	N/A
Construction	Casing	Aluminium
	Dimensions	Φ122mm×106mm (Φ4.8"×4.17")
	Net Weight	0.39kg (0.86lb)
	Gross Weight	0.51kg (1.12lb)

ORDERING INFORMATION

0000000 OPA2ED-MF



TEL
+44 (0) 118 912 5000

