

VLI-4BL28V12IRS

4MP H.265 BULLET CAMERA WITH
MOTORISED LENS AND 30M IR ILLUMINATION



KEY FEATURES

4MP bullet

30m IR illumination

2.8-12mm motorised lens

IP67 ingress protection

H.264/H.265 triple streaming

NDAA Compliant

The VLI-4BL28V12IRS 4MP IP67 bullet packs plenty of features and functionality into its robust but aesthetically designed housing. The bullet can deliver up to 3 streams in multiple formats including H.264, whilst the latest H.265 technology reduces the levels of bandwidth and storage required by the recording solution. Integrated motorised lens, IR illumination, MicroSD card edge storage and PoE, the camera has ROI coding function. This function allows the camera to continually analyse the scene, adding more compression to areas of low interest with no motion whilst applying lower levels of compression to areas where motion is present, as a result showing higher definition in these areas. This means that lower bandwidth is required for transmission and less storage is required on the NVR.

To learn more about this product range please visit vista-cctv.com.



TEL
+44 (0) 118 912 5000

* To scan the QR code, make sure your phone/device has a suitable reader. Most modern Android and iOS smartphone cameras will automatically scan the code and provide the product's URL link, which will open from the device's web browser.



TECHNICAL SPECIFICATION

Model	VLI-4BL28V12IRS
CAMERA	
Image Sensor	1/2.7" CMOS
Image Size	4MP - 2560x1440
Electronic Shutter	1/25 s - 1/100,000s
Min. Illumination	0.011 lux @F1.2, AGC ON; 0 lux with IR, 0.016 lux @ F1.4, AGC ON; 0 lux with IR
Lens	Motorised 2.8 - 12 mm @F1.4
FOV	H: 94° - 35.7°, V: 62.2° - 20.5°
IR Distance	30 - 50M
WDR	Digital WDR
Day & Night	ICR auto switch
BLC Mode	BLC/HLC/DWDR
IMAGE	
Video Compression	H.265/H.264
Resolution	4MP (2560x1440), 3MP (2304x1296), 1080P (1920x1080), 720P (1280x720), D1, CIF, 480x240
Main Stream	4MP/3MP/1080P @30fps
Sub Stream	720P @15fps, D1/CIF @30fps
Third Stream	D1/CIF/480x240 @30fps
Bit Rate	64 Kbps - 5 Mbps
Bit Rate Type	VBR/CBR
ROI	Supports ROI coding, each ROI to be configured separately
INTERFACES	
Network	RJ45
SD card	Up to 128GB
Factory Reset	Hardware
FUNCTIONS	
Remote Monitoring	Web browsing
Online Connection	Support simultaneous monitoring for up to 4 users Support multi-stream real time transmission
Interface Protocol	ONVIF Profile S
Smart Alarm	Motion detection; SD card full; SD card error
Intelligent Analytics	Exception, Line Crossing, Intrusion
OTHERS	
Power Supply	DC12V/PoE
Power Consumption	< 9W
Operating Environment	-30°C - 60°C (-22°F-140°F)
Humidity	less than 95 % (non-condensing)
Dimensions	Φ 80.5x80.5x217.7mm
Weight	Approx. 650g
Ingress Protection	IP67

MODELS IN THIS RANGE

0874860 VLI-4BL28V12IRS
4MP H.265 Bullet camera with motorised lens and 30m IR illumination

ASSOCIATED PARTS

0870400 VL-BLJB
Junction Box for VLI-4BL28V12IRS

0870410 VL-EPMA
Bracket Mount for VLI-4BL28V12IRS



No liability will be accepted by Vista for any errors or omissions in this information | Subject to change without notice.

DS - VLI-4BL28V12IRS - Version 1



TEL
+44 (0) 118 912 5000

