

## DX Series

**The DX Series from CDVI offers high quality, fail secure locking with follower and provision for a euro-cylinder override.** Easy to install, with a simple operation, the DX Series is a high performance and versatile lock to suit many requirements.

Unusually, for a lock of this type, power is not required on the door leaf. The clever design of operation means the keeper houses the electronics, so there is no need for door loops etc.

The unit operates at 12V ac/dc, consuming 1.25A during the operation of releasing the lock - any failure in available power will result in the lock failing in the secure position, but the follower and/or euro-cylinder provision will always allow a manual override.

The backset of the lock is 22mm (DX22), 32mm (DX32) or 50mm (DX50S), and any standard euro-cylinder can be used including thumb-turn etc.

Because of the method of locking, the DX Series can be used on both single and double action doors.



### Overview

- Fail secure lock
- 22mm, 32mm or 50mm backset
- Follower provision
- Double action doors
- Euro cylinder provision
- Reliable lock technology
- 5 year warranty

## DX Series - Technical Specifications

### Product Specifications

Compliance: CE, ROHS & WEEE

Warranty: 5 years return to manufacturer

### Electrical Specifications

Voltage: 12Vac/dc

Current: 1.25A

### Dimensions

Dimensions - lock: 210 x 23 x 50mm

Dimensions - keeper: 210 x 33 x 33mm

Backset: 22mm (DX22), 32mm (DX32) or 50mm (DX50S)