



Description:
 Grade 2 Class II
 4 Terminal Flush Tampered Quickfit
 Contact With Rectangular Plate.

Operating Gap:
 0-15mm (Approx)

Material:
 ABS

Tamper:
 Microswitch

Magnet:
 Ferrite or Alnico V

Contact Material:
 Rhodium

Switching Current
 Reed rated @ 200vDC 50mA.
 Tamper Switch rated @ 30vDC 50mA

Temperature Range:
 -40°C to +50°C

Colours:
 White (No Suffix)
 Brown (Suffix B)

Fixing Screws Provided

Installation:

Connect the REED wires to the NICKEL terminals.

Connect the TAMPER wires to the BRASS terminals.

The operating distance for non magnetic materials is approx. 0-15mm.

Note: Mounting on metal surfaces reduces the functionality, according to the metal type and thickness.



KNIGHT
 FIRE & SECURITY PRODUCTS LTD
<mailto:info@knightfireandsecurity.com>

Unit 84 Seawall Road Ind. Estate
 Cardiff UK CF24 5TH
 Tel: 0 (00 44) 29 20 48 81 29
 Fax: 0 (00 44) 29 20 48 91 32

Drawing No: **A45**
 Drawn: *Chris Moorman*
 Date: *21/06/10*

All dimensions in mm
 Do not scale



© [Knight Fire & Security Products Ltd](http://knightfireandsecurity.com)
 All cases of TM Infringement will be pursued.