

## TECHNICAL DATA SHEET

# 0162

## Heavy Duty Strike



### KEY FEATURES

- No frame cutting required – Surface Mounted
- Higher grade stainless steel ensures superior keeper strength
- Accommodates exit devices with latch projections from 1/2" to 3/4" (12.7mm - 19.1mm)
- Ensure proper latch alignment with horizontal adjustment up to 1/4" (6.4mm) to compensate for door misalignments
- Field selectable voltage input –12 or 24VDC and 12 to 24VAC (even 11 to 16VAC)
- Horizontal solenoid prevents manipulation from vibration

## TECHNICAL DATA SHEET

### TECHNICAL SPECIFICATION

Model Number	0162
Latch Monitoring	NO
Fitting (Frame)	Surface Mounted
Door Type Frame	Hollow Metal, Aluminum, Wood
Operation	Fail Locked
Operating Voltage	Field selectable voltage input 12 or 24VDC and 12 to 24VAC (even 11 to 16VAC)
Current Consumption	300mA @ 12VAC or 500mA @ 12VDC 640mA @ 24VAC or 240mA @ 24VDC 350mA @ 11VAC or 500mA @ 16VAC
Holding Force	680Kg Static
Fire Rating	NO
Other Certification	UL1034 Burglary Resistant , CE
Guarantee	5 Yr Limited Warrantee
Body Size (WxHxD)	44.5 x 228.6 x 19 mm
Short Face Plate Dimensions (WxHxD)	31.75 x 123.83 x 2.8 mm
Long Face Plate Dimensions (WxHxD)	31.75 x 174.63 x 2.8 mm
Weight	907g

Features and specification are subject to change for further improvement without any notice.