



1621

SIMPLEBUS 2W AUDIO UNIT WITH LED, IKALL SERIES



Speaker unit for 2-wire systems complete with terminal block and audio control with echo-cancelling, sealed-unit loudspeaker, electret microphone and front-mounted loudspeaker volume control. Complete with microprocessor and 8-position dip switch for programming calls to users. On-board electronic lock-release function (3A) plus C, NC, NO contacts for 10A relay. Timed lock-release input and door open indication. Compatible with power supply unit art. 1210. Dimensions: 102x55x38 mm.



1621

SIMPLEBUS 2W AUDIO UNIT WITH LED, IKALL SERIES

GENERAL SPECIFICATIONS

| | |
|---------------------------------------|--------------------------------------|
| Audio system: | Yes |
| Audio/video system: | Yes |
| Power supply voltage: | 35 ÷ |
| Absorption in standby (mA): | 53 ÷ |
| Absorption during call (mA): | 68 ÷ |
| Absorption during communication (mA): | 90 ÷ |
| Clamps: | L L V+V- RTE DO GND SE- SE+COM NC NO |
| Microphone: | Yes |
| Loudspeaker: | Yes |
| Loudspeaker volume control: | Yes |
| RH max operating humidity (%): | 75 ÷ |

COMPATIBILITY

| | |
|----------------------------------|-----|
| Building Kit audio/video system: | Yes |
|----------------------------------|-----|