

Key switches

A range of 2 or 3 position key switches mounted on a stainless steel plate, and available as flush or surface.







Overview

- Stainless steel
- Supplied with 2 keys (round version)
- 2 or 3 position versions
- Standard or architrave format
- Keyed alike or keyed to differ
- Momentary or maintained versions
- Surface, option of flush
- Euro profile option (cylinder not included)



Key switches - Technical Specifications

Product References

Standard 2 position

KEY-SSMAKA Surface standard key switch, 2 position, maintained, keyed alike **KEY-SFMAKA** Flush standard key switch, 2 position, maintained, keyed alike **KEY-SSMAKD** Surface standard key switch, 2 position, maintained, keyed to differ Flush standard key switch, 2 position, maintained, keyed to differ **KEY-SFMAKD KEY-SSMOKA** Surface standard key switch, 2 position, momentary, keyed alike **KEY-SFMOKA** Flush standard key switch, 2 position, momentary, keyed alike **KEY-SSMOKD** Surface standard key switch, 2 position, momentary, keyed to differ **KEY-SFMOKD** Flush standard key switch, 2 position, momentary, keyed to differ

Architrave 2 position

KEY-ASMAKA
KEY-AFMAKA
KEY-AFMAKA
KEY-ASMOKA
KEY-AFMOKA
Surface architrave key switch, 2 position, maintained, keyed alike
Surface architrave key switch, 2 position, momentary, keyed alike
Flush architrave key switch, 2 position, momentary, keyed alike

Standard 3 position

KEY-SS3MOKD Surface standard key switch, 3 position, momentary, keyed to differ **KEY-SF3MOKD** Flush standard key switch, 3 position, momentary, keyed to differ

EURO profile

KEY-SSEUMA
KEY-SFEUMA
KEY-SSEUMO
KEY-SSEUMO
KEY-SFEUMO
KEY-SFEUMO
Surface euro key switch, momentary (cylinder not included)
Flush euro key switch, momentary (cylinder not included)
Flush euro key switch, momentary (cylinder not included)

Dimensions

Dimensions - standard surface: 85 x 85 x 30mm

- Dimensions standard flush: 85 x 85 x 2mm
- Dimensions architrave surface: 85 x 38 x 29mm
- Dimensions architrave flush: 85 x 38 x 2mm