



AGT is the handset video intercom with 5" LCD display which ensures brilliant colors and excellent video quality.

Featured by sleek lines and soft touch buttons with concealed indicator LEDs in a matte white finish.

Handset with essential lines for excellent ergonomics and magnetic hang-up that eliminates the risk of falling or incomplete contact.

The OSD function allows you to manage the image color, brightness and contrast.

MAIN FUNCTIONS

- 5" color display with OSD
- Handset with magnetic hang-up
- Concealed LED signal
- Soft-touch buttons
- Self-inserting video from entry panels
- Master/Slave function and video relaying between extensions function for simultaneous calls.



Version for the hearing impaired



Handset



5" display






Wall mounted
44.5 mm thick
(without 21 mm handset)

It includes a bracket for wall mounting on horizontal or vertical 503 box, on 506E box and Ø 60 mm round box.



THE COMPLETE RANGE

Code	Description	
Handset video intercoms for X1 systems		
AGT V 840CF-0020	Handset video intercom with soft-touch buttons, 5" LCD display, white. Wall monitor with 5" color LCD display equipped with OSD for adjusting video parameters (brightness, color, contrast). The 4 main touch buttons are used to manage the primary functions such as door opening, self-insertion of entry panel videos, ringtone adjustment/exclusion (with signaling LED when excluded) and the sending of a programmable auxiliary control. It allows managing the "gate opener" function and displays the status of the gate controlled by means of a signaling LED. It includes a bracket for wall mounting on horizontal or vertical 503 box and on Ø 60 mm round box. Compatible with the X1 and XIP systems.	
AGT V BF 840CF-0030	Handset video intercom with soft-touch buttons, 5" LCD display, white. Hearing aid function for hearing aid users. Wall monitor with 5" color LCD display equipped with OSD for adjusting video parameters (brightness, color, contrast). The 4 main touch buttons are used to manage the primary functions such as door opening, self-insertion of entry panel videos, ringtone adjustment/exclusion (with signaling LED when excluded) and the sending of a programmable auxiliary control. It allows managing the "gate opener" function and displays the status of the gate controlled by means of a signaling LED. With built-in audio-frequency induction system for hearing aids, in the "T" position. It includes a bracket for wall mounting on horizontal or vertical 503 box and on Ø 60 mm round box. Compatible with the X1 and XIP systems.	
Handset video intercoms for 200 systems		
AGT V200 840CF-0010	Handset video intercom with soft-touch buttons, 5" LCD display, white. Wall monitor with 5" color LCD display equipped with OSD for adjusting video parameters (brightness, color, contrast). The 4 main touch buttons are used to manage the primary functions such as door opening, self-insertion of entry panel videos, ringtone adjustment/exclusion (with signaling LED when excluded) and the sending of an auxiliary control. It includes a bracket for wall mounting on horizontal or vertical 503 box and on Ø 60 mm round box. Compatible with 200 system.	

AGT V 840CF-0020



PLUS

- Program melodies depending on the type of call
- Display color, brightness and contrast adjustment via OSD
- Adjust/exclude ringtone, with alert LED when set to exclude mode
- AUX2 for auxiliary functions and call to the porter
- Latch function (gate opener) for checking the status of external automations
- Automatic door-opener function



AGT V BF 840CF-0030



PLUS

- Program melodies depending on the type of call
- Display color, brightness and contrast adjustment via OSD
- Adjust/exclude ringtone, with alert LED when set to exclude mode
- AUX2 for auxiliary functions and call to the porter
- Latch function (gate opener) for checking the status of external automations
- Automatic door-opener function
- Equipped with Audio Induction Loop technology, which allows the use of the video intercom even for hearing aid wearers



TECHNICAL CHARACTERISTICS

MODELS	AGT V	AGT V BF
Dimensions (mm)	204 x 190 x 44,5	204 x 190 x 44,5
Power supply by BUS (V)	15 ÷ 20 DC	15 ÷ 20 DC
Absorption by BUS (mA)	175	175
Local power supply (V)	-	-
Local absorption (mA)	-	-
Consumption in stand-by mode (mA)	<1	<1
Operating temperature (°C)	+5 ÷ +40	+5 ÷ +40
Protection rating (IP)	30	30
Video standard	PAL/NTSC	PAL/NTSC
Color	White	White

AGT V200

840CF-0010



PLUS

- Program melodies depending on the type of call
- Display color, brightness and contrast adjustment
- Adjust/exclude ringtone, with alert LED when set to exclude mode
- Up to 6 intercom calls



Accessories

AGT KT V 840XC-0150

Desktop stand for video entry panels of the AGT V, Agata Video, Perla Video and Opale series.

Plexiglass 10 mm-thick stand, supplied with white RJ45 cable and terminal board cover with PMMA laminate - metallic gray.



TECHNICAL CHARACTERISTICS

MODELS	AGT V200
Dimensions (mm)	204 x 190 x 44,5
Power supply by BUS (V)	-
Absorption by BUS (mA)	-
Local power supply (V)	14 ÷ 17,5 DC
Local absorption (mA)	95
Consumption in stand-by mode (mA)	<12
Operating temperature (°C)	+5 ÷ +40
Protection rating (IP)	30
Video standard	PAL/NTSC
Color	White