Suprema BioMini & SDK

High Performance PC Fingerprint Solution



BioMini Suprema's fingerprint-based PC solution has been designed specially to provide high level biometric security for desktops as well as complex network environments. Our latest range of high-performance fingerprint USB scanners are supported by powerful software development kit (SDK) which features Suprema's award-winning algorithm, ranked top in FVC and NIST MINEX tests. Suprema PC solution provides unrivalled versatile platform for development to leading security companies, system integrators and hardware manufacturers.



suprema BioMini & SDK

High Performance PC Fingerprint Solution



BioMini Front View



BioMini Side View



BioMini SDK

The BioMini SDK enables a user to develop fingerprint applications quickly and easily.

Contents:

- Fingerprint algorithm library for PC Windows or Linux
- Sample application program with source code (VC, VB, C#, VB.NET, Java) $\label{eq:condition} % \begin{subarray}{ll} \end{subarray} % \begin{su$
- Technical documents
- Fingerprint scanner





- World's best performing fingerprint algorithm: Top results in NIST MINEX tests and FVC
- FIPS 201 certified template extractor and matcher
- NIST certified interoperable template format standards (ANSI-378/ISO19794-2)
- Image Compression Standard (WSQ)
- Fast matching speed: 100,000 match within a second*
 Multi-threaded code design fully utilizing multi-core CPU power



- Plug and play USB 2.0 high speed interface
- Supports multiple device handling
- 500 dpi optical fingerprint sensor
- Scratch free sensor surface



- BioMini SDK for easy application software development
- Supports MS Windows and Linux
- Supports multiple programming languages

*with Intel Core2Duo 2.13GHz

BioMini Specifications	
Fingerprint Sensor	Optical (Scratch free sensor surface)
Resolution	500 DPI / 256 gray
Sensing Area	16 x18 mm
Image Size	288 x 320 pixels
Interface	USB 2.0 High speed / Full speed, Plug & Play
O/S	Microsoft Windows, Linux
Operating Temperature	-10~50℃
Certification	CE, FCC, KCC, WHQL
Size	66 x 90 x 58 mm (W x L x H)

*Operation of BioMini Plus under direct sunlight can result a failure in image capturing.

SDK Specifications	
Template Size	1024 Bytes (Configurable)
Enrollment Time*	< 0.1 second
Verification Time*	< 0.1 second
Identification Time*	100,000 matches per second
Database	Microsoft Access
Encryption	256 bit AES
Supported Platforms	Windows 7 / Vista / XP / 2000 / ME / 98, Linux

*with Intel Core2Duo 2.13GHz

Suprema Inc.

16F Parkview Office Tower, Jeongja, Bundang, Seongnam, Gyeonggi, 463-863 Korea

Tel: +82-31-783-4502, **Fax**: +82-31-783-4503

E-mail: sales@supremainc.com **Homepage**: www.supremainc.com

