2-Wire Indoor Monitor CDV43



CDV43 is a simple and inovative design with a 4.3 inch TFT screen- enusering high quality performance. The intutive graphic menu can control each of the function included in the monitor

Multi Language supported:

The operating languages can be customisedsatisfying different customer needs.

Touch sensor buttons:

Allows smooth activation combined with great flexibility with high sensitivity. All functions may be controlled by these buttons.

Slim & ultra-thin design: Only 12mm deep.

Plexiglass front panel:

The front panel is made from plexiglass which is scratch resistant.

Features

- Hands-free communication
- 4.3" colour TFT screen
- Magnetic bracket mount
- Plexiglass front panel
- Touch sensor buttons
- Slim & ultra thin design

Main Menu Monitor by Select Intercom Call Doert Call Don't Disturb

Advanced features:

Calls can be transferred to mobile phones via the CDV-GSM unit. Options include No Divert, Divert if no answer, simultaneously call to handset and mobile phones! (requires CDV-GSM unit)

Technical specification

Power supply for indoor monitor: DC 20~28V

Power consumption: Standby 0.17W; Working status 4.7W

Monitor screen:4.3-inch digital color TFTDisplay Resolutions:480(R, G, B) x 272 pixelsVideo signal:1Vp-p,75Ω, CCIR standard

Wiring: 2 wires, non-polarity

Monitor time: 40 seconds Talking time: 90 seconds

Dimensions: $137(H) \times 137(W) \times 17(D) mm$

