



COBRA *elite v*

HD-TVI ELITE 32 CHANNEL

HDT-V 32E

KEY FEATURES

- 32ch (48ch with IP cameras) real-time HD 1080P recording
- Ultra HD 4k monitor output, switchable to 1080P (HDMI)
- Full Hybrid DVR (HD-TVI, AHD, HD-CVI, Analogue & IP Cameras)
- Up to 36TB Storage on Elite Model (HDT-V16E / HDT-V 32E)
- User-friendly GUI & Design
- Smart & Event Search – saving you time when looking through footage!
- Sensor, Motion, Audio Detection
- Two-way Audio Communication Support
- Up the Coax Telemetry for compatible PTZ / Auto Focus camera models
- Auto port forwarding - Free DDNS
- Various Network Software – VMS, RMS, Web Viewer, Mac Viewer
- Fast Smartphone access full features live & playback
- Supplied with mouse and IR remote

HDT-V 32E

SPECIFICATION

COBRA elite v

| | |
|--------------------|--|
| Model | HDT-V 32E |
| System | |
| OS | Embedded Linux |
| Language | Chinese, Chinese(S), Dutch, English, French, German, Hebrew, Hungari, Italian, Japanese, Korean, Latvian, Persian, Polish, Portuguese, Russian, Spanish, Sweden, Turkish, Arabic |
| Time Accuracy | 5ppm (12.5sec/month) |
| Time Sync. | NTP, GMT, DST, Time Server |
| User | 15 Users (Admin., User1 ~ User14) |
| Camera | |
| IP Camera | ONVIF Profile S |
| Video | |
| System | NTSC / PAL |
| Input | 32 BNC / 16 BNC |
| IPC Input | 16 IPC / 8 IPC |
| Output Interface | HD-MI, VGA, BNC |
| Spot | HD-TVI spot, SD spot |
| Audio | |
| Input Interface | 16 RCA |
| Output Interface | 1 HD-MI, 1 RCA |
| Video Recording | |
| Compression | H.264 |
| Speed | 15fps/ch, 30fps/ch |
| Resolution | TVI(720p, 1080p, 3MP, 4MP, 5MP, 4K), AHD(720p,1080p, 3MP), CVI(720p, 1080p), Analog SD(960H), IP(Max. 4MP) |
| Quality | 5 Levels |
| Audio Recording | |
| Compression | G.711u |
| Playback | |
| Search | Go to first rec. time, Go to last rec. time, Go to last search time, Calendar, Log viewer, Smart search, Multi-time & day search, Event search |
| Mode | Event only playback, Backward, Pause, Frame by frame, Speed up (x1 ~ x32, x300) |
| Network | |
| Interface | RJ45 (Ethernet 10/100/1G) x 2 |
| Compression | H.264 |
| Speed | Max. 1080p 15fps/ch |
| Resolution | Max. 2MP(1080p) |
| Backup | |
| Interface | USB, Network |
| Format | RMS, AVI |
| Alarm | |
| Post-Alarm | 5sec~5min |
| Motion Grid | 32 x 24 |
| Alarm Action | E-mail, Event Popup, Buzzer, Relay, PTZ Preset, Remote VMS, Front LED |
| Input / Output | 16/4 - NC/NO |
| Display | |
| HD-MI | Full HD, XGA |
| TV | SDTV(720x480) |
| Mode | 32/16/9/4/1/SEQ/BIG - LIVE, 32/16/9/4/1 - P.B 16/9/4/1/SEQ/BIG - LIVE, 16/9/4/1 - P.B |
| External Interface | |
| PTZ / Keyboard | 2 RS485 - Terminal Block |
| ATM / POS | RS232C - Terminal Block, Ethernet POS |
| Storage | |
| Primary | 6 HDD |
| External | 2 eSATA |
| General | |
| Power Supply | 90~250V, 50/60Hz |
| Consumption | 80W |
| Operating Temp. | 5 ~ 40°C |
| Humidity | 10 ~ 80% |
| Weight w/o HDD | 8Kg |
| Dimension | 440 x 88 x 430 mm |
| Certification | CE, FCC, RoHS Compliance |

HDT-V 32E