## **DATA SHEET**

COD. 2638

#### STYLE BASIC HANDSET FOR A/V SYSTEMS

Audio only handset for Simplebus cabling with volume control, privacy of speech, call tone privacy, door open push button and supplementary push button for porter switchboard calls. Complete with dip-switch with 8 positions for selection of the desired user code. There are a total of 6 additional programmable buttons for various functions such as turning lights on and opening gates. The handset is designed for audio/video systems only

Dimensions: 95X215X58mm



#### **Main specifications**

System:	SBT S2(2-wires)
Audio system:	Yes
Audio/video system:	Yes
Wall-mounted:	Yes
Desk base-mounted:	Yes
Hands-free function:	No
Induction loop function:	No
Product colour:	White RAL9003
Product colour: Interchangeable cover:	White RAL9003
Interchangeable cover:	No
Interchangeable cover: Sensitive Touch technology:	No No
Interchangeable cover: Sensitive Touch technology: Total buttons:	No No 2

#### **Functions**

Actuator control function:	Yes
Switchboard call function:	Yes
Panic call:	Yes
Intercom function:	Yes
Selective intercom call:	Yes
Call to multiple addresses:	Yes
Call to group addresses:	Yes
Call forwarding:	Yes
Privacy function:	Yes
Redial:	Yes



# **DATA SHEET**

Floor door call function:	Yes
Electronic bell:	Yes
Mechanical ringtone:	No
Customisable ringtone:	No
Alarm function:	No
Privacy conversation function:	Yes
Key button function:	Yes
Full Duplex hands-free function:	No

### **Hardware specifications**

Customisable housing:	No
Type of finish:	PLASTIC

## Settings

Loudspeaker volume control:	Yes	
Microphone volume control:	Yes	
Ringtone volume control:	Yes	

#### **General** info

Product height (mm):	215
Product width (mm):	95
Product depth (mm):	58

## Compatibility

Video door entry family:	Yes	
Simplebus Top system:	Yes	
Simplebus Color system:	Yes	
Simplebus 2 system:	Yes	

## **Technical specifications**

Power supply voltage:	22÷28Vdc
Absorption:	1
Maximum current absorption (mA):	200
Microphone:	9,6x6,9mm omni-direction
Loudspeaker:	50mm 50OHM
IP Rating:	30
Operating temperature (°C):	-5÷40
Product weight (g):	0,417
Clamps:	L L CFP CFP C3 P3 S- S+

### **Packaging**

Single pack height (mm):	65
Single pack width (mm):	235



# **DATA SHEET**

Single pack weight (Kg):	0,417
Single pack depth (mm):	90
Single pack volume (dm3):	1,375

