DATA SHEET

сор. 1456G

THIRD PARTY HOME AUTOMATION INTERFACE

Interface allowing the connection of third party Home Automation devices. 1 port for connection to part. 1440 and 4 ports for connection to the VIP monitor, and other network devices on the private network. Dimensions 70x90x62 mm (4 DIN modules).



Compatibility		
Video door entry family:	Yes	
Vip system:	Yes	
Mounting/Installation		
DIN rail mounted:	Yes	
DIN modules (no.):	4	
Connectivity		
Ethernet ports:	Yes	
Technical properties		
Temperature range (°C):	-5°C/+50°C	
Temperature range (°C):	-5°C/+50°C 2W	
Temperature range (°C): Electrical specifications		
Temperature range (°C): Electrical specifications Absorption:		
Temperature range (°C): Electrical specifications Absorption: General info	2W	
Temperature range (°C): Electrical specifications Absorption: General info Product height (mm):	2W 62	
Temperature range (°C): Electrical specifications Absorption: General info Product height (mm): Product width (mm):	2W 62 70	
Temperature range (°C): Electrical specifications Absorption: General info Product height (mm): Product width (mm): Product depth (mm):	2W 62 70 90	
Temperature range (°C): Electrical specifications Absorption: General info Product height (mm): Product width (mm): Product depth (mm): Product depth (mm):	2W 62 70 90	
Temperature range (°C): Electrical specifications Absorption: General info Product height (mm): Product width (mm): Product depth (mm): Product depth (mm): Single pack height (mm):	2W 62 70 90 76	



The technical specifications are subject to variations without warning

Single pack volume (dm3):

0,627

