

DOOR ENTRY SYSTEMS & KITS

POWER SUPPLIES AND ACCESSORIES

1/3



1998NA

AUDIO PORTER SWITCHBOARD. S1





Audio porter switchboard in desk version for Simplebus 1 system with microswitch keypad and 32-character alphanumeric display. Ergonomic handset with easier hangup, thanks to concealed magnetic panels. Allows the code and name of the called and calling users to be displayed, keeping unanswered calls stored in the memory. Manages Day/Night mode and user/user intercom service. Allows management of alarm indications originating from users. Up to 1000 users can be saved. Supplied with a removable cable with connection hub. 24 VAC power supply with art. 1195. Dimensions (L x H x D): 225x100x225 mm.



DOOR ENTRY SYSTEMS & KITS

POWER SUPPLIES AND ACCESSORIES





1998NA

AUDIO PORTER SWITCHBOARD. S1	
COMPATIBLE SYSTEMS	
Audio/video Simplebus 1	Yes
Audio Simplebus 1	Yes

DISPLAY	
Display type	32-character alphanumerical display

	AUDIO FEATURES
Technologies implemented	Full-Duplex

ELECTRICAL CHARACTERISTICS	
Max/min absorption (mA)	20 ÷ 200
Type of power supply	External power supply

HARDWARE FEATURES	
Visual signalling	Yes
Acoustic signalling	Yes
Number of push-buttons (n°)	36
Number of outputs (n°)	2

ENVIRONMENTAL AND COMPLIANCE FEATURES	
Environmental class	

	MAIN FUNCTIONS
Door opener	Yes

GENERAL FEATURES	
Call type	Digital
CE certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007, EN 61000-6-3:2007+A1:2011)
Type of buttons	Mechanical



DOOR ENTRY SYSTEMS & KITS

POWER SUPPLIES AND ACCESSORIES



3/3

1998NA

AUDIO PORTER SWITCHBOARD. S1	
	MAIN FEATURES
Height (mm)	90
Depth (mm)	230
Product weight (g)	1500
Operating temperature (°C)	-5 ÷ 40
Operating humidity (RH max) (%)	25 ÷ 90
Supply voltage	24
Maximum current absorption (mA)	200
SOFTWARE/FIRMWARE SPECIFICATIONS	

SOFTWARE/FIRMWARE SPECIFICATIONS	
No. of storable users (n°)	1000

	GENERAL DATA
Type of finishing materials	ABS

FUNCTIONS	
Alarm function	Yes
Actuator control function	Yes
Intercom function	Yes
Key button function	Yes

	COMPATIBILITY
Simplebus 1 audio system	Yes

	CONNECTIVITY
RS232 ports (n°)	1