DOOR ENTRY SYSTEMS & KITS



IKALL METAL

1/2



3348BM

ELECTRONIC KEY MODULE, IKALL METAL SERIES



Digital electronic key module with LED keypad backlighting. Blue, white and off lighting options; stainless steel finish. When a number with between 1 and 8 digits is entered on the keypad, two relays (10A) are activated, allowing the operation of electric door locks or other devices. Dimensions 112x89.5x40 mm.

COMELIT

DOOR ENTRY SYSTEMS & KITS

IKALL METAL

2/2



3348BM

ELECTRONIC KEY MODULE, IKALL METAL SERIES		
	MAIN FEATURES	
Supply voltage	12VDC/12VAC (stand-alone) / Simplebus	
Operating humidity (RH max) (%)	25 ÷ 75	

	GENERAL DATA
Height (mm)	89.5
Width (mm)	112
Depth (mm)	40
Type of finishing materials	Plastic/Steel
Product color	Steel
Operating temperature (°C)	-5 ÷ 55

	COMPATIBILITY
Simplebus 2 audio/video system	Yes
Simplebus 2 audio system	Yes
Building Kit audio/video system	Yes
Simplebus 1 audio system	Yes
Access Control system	Yes

ELECTRICAL SPECIFICATIONS	
Absorption in stand-by (mA)	20
Absorption with 1 bistable relay activated (mA)	45
Absorption with 2 bistable relays activated (mA)	65

MOUNTING/INSTALLATION		
Flush-mounted	Yes	