



GAHDB21W

2MP Waterproof AHD Mini Bullet Camera

GAHDB21W is a 2.3MP AHD Bullet Camera with an 3.6mm fixed lens, built-in OSD and mount. 12VDC



GAHDB21W

Key Features

- 2MP, 1080P
- 3.6mm Fixed Lens
- For Indoor or Outdoor Use
- Built In OSD Control Board
- Optional Sunshield
- 12VDC
- WDR (Wide Dynamic Range)
- Defog (Visibility Enhancement on Low Contrast)
- IP66 Waterproof
- Max. 500M Transmission Range
- 1/3" Sony 2MP CMOS Sensor

Accessories

- **PSU1SM** - In-Line DC12V 1A Output, Regulated Switch Mode PSU, with Fixing Mount
- **GFPC12** - DC12V Power Connector Jack (Female)
- **GMPC12** : DC12V Power Connector Jack (Male)



Technical Specification

Model Number	GAHDB21W
Image Device	1/2.9" 2.3 Megapixel Sony CMOS
Scanning System	Progressive
Resolution	AHD: 1080p, 720p and CVBS:1280H
Lens	3.6mm Fixed
Total Pixel	2000 (H) x 1121 (V) Approx 2.24 Megapixel
Effective Pixel	1984 (H) x 1105 (V) Approx 2.19 Megapixel
Shutter Speed	Auto/Manual (1/30(1/25) - 1/60000) / Flicker
Minimum Illumination	Colour DSS: 0.002 Lux, B&W DSS :0.00 Lux
S/N Ratio	>80dB
Day / Night	Auto / Colour / B&W / EXT
Sens-Up	x2 / x4 / x8 / x16 / x32
Smart IR	Off/On
White Balance	Auto/Auto Ext/ Preset/Manual
Mirror	Off/H/V/H&V
D-Zoom	x1~ x8
DNR	Off / Low / Middle / High
Privacy	Off/On (16 Points)
Motion	Off/On (16 Points)
Shading	0 - 100%
Defog	Off/On
IP Rating	IP66 Waterproof
D-WDR / BLC / HLC	Off / WDR (Low / Middle / High) / BLC / HLC
Coaxial Communication	Pelco-C Protocol or OSD
Language	ENG, GER, FRA, ITA, SPA, POL, RUST, POR, NED and TUR
Video Output	AHD / CVBS
Power Supply	DC12V
Power Consumption	Max 1.8W (150mA)
Operating Temperature	-10 °C - +50 °C
Dimensions (ø x L)	20.8 x 78.9 (mm)

Genie CCTV reserves the right to change specifications without notice. Please contact your representative to confirm current specifications.

Dimensions (mm)

