



# GIP2SMO/S

## Sideview 2MP IP Camera in a Smoke Detector Case

*The GIPSMO/S is a Sideview 2MP IP Smoke Detector Cameras suitable for Covert Operations.*



GIP2SMO/S Series

### Key Features

- Full HD (1080P) IP Network Camera
- 1/2.7" 2MP CMOS Sensor
- 3.7mm Conical Pinhole Lens
- Digital Day / Night
- H.264 / MJPEG Triple Streaming
- 0.2 Lux (Colour), 0.01 Lux (B&W)
- ONVIF Support
- Motion Recording into Micro SD Memory upto 32GB
- AGC, AE, AWB, BLC
- DC12V, PoE (802.3af)
- Compatible with Wish NVR Range



## Technical Specification

Model Number	GIP2SMO/S
Image Device	1/2.7" 2MP Progressive Scan CMOS Sensor
Lens	3.7mm Conical Pinhole Lens
Scanning System	Progressive
Shutter Speed	1/25 ~ 1/10,000 Sec
Privacy Masking	Yes (1 Zone)
Motion	Yes (1 Zone)
Flip Mode	Horizontal, Vertical
Image Enhance	AGC, AE, AWB, Digital Day & Night
Video Compression	H.264, MJPEG
Audio	N/A
Frame Rate	1st/2nd Stream (H.264) : 25fps @ 1080P / 25fps @ 640 x 480, 3rd Stream (MJPEG) : 5fps @ 1080P
Video Encoding	H.264 / H.264 / MJPEG Triple Streaming
Protocol	HTTP, TCP/UDP/IP, RTP/RTSP, FTP, SMTP, DHCP, NTP, WS-Discovery, ONVIF
Transmission Control	VBR, CBR (512 Kbps ~ 10Mbps)
Interface	Ethernet 10/100 Base-T (RJ45)
Installation & Maintenance	Configuration: IP Search Tool & Web, Upgrade Through WEB Browser
PoE	IEEE Std. 802.3af
Resolution	CIF, VGA, D1, 720P, 1080P
Event	Motion Recording into Micro SD Memory up to 32GB
Operating Temperature	-10°C ~ 50°C, 20% ~ 80%
Power	PoE / DC12V, 1A
Dimensions (W x H x D)	42 x 42 x 21 mm
Weight	100g
Power Supply	DC12V
Power Consumption	Max 1.8W (150mA)
Operating Temperature	-10 % - +50 %

Genie CCTV reserves the right to change specifications without notice. Please contact your representative to confirm current specifications.