



HDUBARTK-R

1 Channel Active Balun Receiver

The 1ch HD analog video UTP Receiver transfers real-time analogue video signal up to 1,200m (CVBS) through Cat5/5e/6 cable, see table below for Transmission distances.



HDUBARTK-R

Key Features

- Up to 1,200m Transmission Distance (With Active Transmitter) (CVBS)
- Compatible with HDCVI, HDTVI, AHD, CVBS Signals
- ESD Protection

Transmission Distance Table (Recommended)

Signal Type	AHD 1080P	HDCVI 1080P	AHD 720P / 960P	HDCVI 720P	HDTVI 720P	HDTVI 1080P	CVBS
Transmission Distance	300m	500m	700m	600m	400m	400m	1200m

Accessories

- HDUBARTK-T - 1 Channel Active Balun Transmitter



Model Number	HDUBARTK-R
Transfer Signal Number	1 Ch Video
Transmission Distance	1,200m (CVBS)
Voltage Input	DC12-20V or AC9-24V
Video Connector	1xBNC (Male)
Cable Pod	1*3 Pin Terminal
Compatible Video Type	AHD, CVBS, HDCVI, HDTV1 Signal
Transfer Bandwidth	0-75MHz
Signal Indicator	Yellow Solid ON : Power Input Normal
Anti-Interference	Green Solid ON : Signal Input Normal
Surge Protection Coaxial Port	>60dB
Surge Protection of Line Connector	2KV Differential-mode 2KV Common-mode Per : IEC61000-4-2
ESD Protection	1a Contact Discharge 6KV 1b Air Discharge 8KV Per : IEC61000-4-2
Operation Temperature	-10°C - 55°C (0-95% Humidity)
Storage Temperature	-45°C - 75°C (0-95% Humidity)
Weight	65g
Dimensions (W x L x H)	45 x 113 x 29 (mm)

Genie CCTV reserves the right to change specifications without notice. Please contact your representative to confirm current specifications.

Dimensions (mm)

