

# LMA-215C

## 21.5" HDMI and VGA LED Monitor with BNC

The LMA-215C is a 21.5" HDMI and VGA LED monitor. The monitor has BNC 2x inputs and 1x output as well as a fast response time of 5ms so no image ghosting. The monitor is also able to continually work for 24/7 and has a built-in speaker and 3D digital noise reduction technology making the LMA-215C perfect for office and monitoring applications.



LMA-21C Front

### **Key Features**

- Full HD 1920 x 1080
- BNC input x2, BNC output x1
- 5ms fast response time
- Built-in 3D comb filter
- 3D digital noise reduction
- HDMI / VGA
- 16:9 grade A panel
- Supports 24/7 continuous
- Desk stand (Detachable)
- Built-in speaker
- Standard and VESA mount options



LMA-215C Back

#### Accessories



BT7510/B Fixed LCD / TFT Wall Mount Bracket



BT7512/B Single Arm Tilt & Swivel Wall Mount Bracket



BT7511/B Tiltable LCD / TFT Wall Mount Bracket



BT7513/B Double Arm Wall Mount Bracket





# Specification

Model Number	LMA-215C
Size	21.5"
Active Display Area	476.64 (W) x 268.11 (H) mm
Display Mode	16:9
LED Type	TFT-LED
Resolution	1920 x 1080
Display Colour	16.7m
Pixel Pitch	0.248 (H) x 0.248 (V) mm
Brightness	350cd/m <sup>2</sup>
Contrast Ratio	1000:1
Viewing Angle	178 (H) / 178 (V)
Response Time	5ms
Backlight	LED
Inputs	HDMI2.0 x1, VGA x1, BNC x2, Audio x1
Outputs	BNC x1, Speaker 2x3W (Stereo)
Colour System	PAL / NTSC / SECAM
OSD Control	Auto adjust, Brightness, Contrast, Horizontal / Vertical position, Clock, Phase, Colour, Language
3D Comb Filter	Yes
Video Noise Reduction	Yes
Power	DC12V ~ 24V, 50/60Hz
Power Consumption	≤20W
Working Temperature	-30°C ~ 85°C
Mounting	Stand mount, VESA mount
MTBF	50000 hours
Certificate Approval	CE,RoHS,CCC,FCC,ISO9000, UL
Dimensions	518.8 (W) x 319.8 (H) mm
Weight	2.32 Kg

Genie Access reserves the right to change specifications without notice. Please contact your representative to confirm current specifications.

## Dimensions (mm)

