LME42MC

42" LED Monitor Plastic Case

AUDIO IN / OUT

COLOUR

HI RES

MULTI LANGUAGE

OSD

VGA / BNC INPUT

HDMI INPUT

WIDE ANGLE VIEW

The LME42MC 42" LED Monitor offers excellent picture quality and a sleek and pleasant design normally associated with higher end units. An impressive 5000:1 contrast ratio and 1920 x 1080 resolution and response time of 8ms gives you the ultimate performance and delivers crisp clear images.

This range of monitors also feature HDMI, VGA & BNC input capabilities providing various connection options. The slim design maximises desktop space and makes a perfect fit for almost any office or commercial application.

Key Features

▶ 1920 (H) x 1080(V) Resolution
▶ Wide Viewing Angle
▶ High Contrast Ratio
▶ Environmental friendly

▶ Built in Speaker
▶ Multi Language OSD
▶ Slim Design
▶ Fast Response Rate

V1.01

RoHS 2002/95/EC   CE

ISO 9001 REGISTERED FIRM

LME42MC

Specifications

Description / Model	LME42MC 42" LED CCTV Monitor
MONITOR SPECIFICATION	
Panel Type	42" 16:9 LED Panel
Case Type	Plastic
Maximum Resolution	1920(H) x 1080(V)
Active Display Area	919.296 (H) x 517.104 (V)
Pixel Pitch	0.0798 (V)x0.2394 (V)mm
Bezel Thickness	Left/Right/Top/Bottom 22mm
Contrast Ratio	5000:1
Brightness	350cd/m2
Response Time	9ms
Viewing Angle	178°/178° (H/V)
Display Colours	16.7M
Video Synchronization	Yes
PC Compatible Frequency	30-60KHz(H)/56-75KHz(V)
Adjustable Colour Temp	9300K/6500K/5800K/User
Video Compatiblity	NTSC/PAL
Aspect Ratio	16:9
VGA Auto Frequency correction	Yes
Speaker	2 x 5w
Number of Speakers	2
Sound Demodulation	Audio, Stereo
Mute	Yes
Work Humidity	5% - 80%
Work Temperature	-10° /+50°
Volume +/- Power On/Off	Yes
Power Supply	AC
Voltage	AC110V - 240V 50/60 Hz
Power Consumption	<80W
Video Interface	1x BNC Composite In,1x BNC Composite Out, 1xVGA, 1xHDMI
Audio Interface	1x PC Audio
Power Interface	DC in x 1
Termination	75 Ohms
Safety & EMC Certification	CE, RoHS, FCC-DOC
Vesa Standard Mount	200 x 200mm, 200 x 400mm
Stand Type	Desktop
Colour	Black
Button Position	Rear Face, Right Bottom
Packing Dimension	1155 x 245 x 760
OSD Controls	Contrast, Brightness, Colour,Sharpness, Colour Temperature
OSD Language	English, German, Italian, Spanish, French, Russian, Portuguese and Polish
Accessories	VGA Cable, User Manual, Audio Cable, Power Adapter, Power Lead

NB. Specification subject to change without notification

V1.01

Unit 9 Garrick Road Industrial Estate, Irving Way, London, NW9 6AQ, England
tel: technical support +44 (0)20 8732 3350   +44 (0)20 8732 3332
fax: +44 (0)20 8202 3387   www.cbceurope.com