



The performance features at a glance

- H.264 & MJPEG
- 3.0 Megapixel
- Mechanical Day-/Nightswitching
- 3mm - 10mm Vario lens
- Integrated IR-LEDs
- Dualstream
- Videoanalytics

High versatility

The LN-B2M bullet camera in its compact casing is primarily configured for outdoor use. In this context it features safety class IP66. High performance IR LEDs also provide sufficient light, also when it is dark.

Outstanding advantages

With a resolution of up to 2048 x 1536 both domes provide high quality and detailed images. In this context it is possible to show up to 22 images per second. In the full HD resolution the total is 30.

High-performance technology

In addition to h.264, MJPEG is also available as a compression procedure. The latter provides 15 images per second, even at full HD resolution. A range of event functions keep the user continuously up to date on the system status.

Other special features

The integrated video analysis enables an even more detailed surveillance and control of the surrounding areas and its scope therefore extends beyond the integrated movement sensor feature. A privacy mask function is also incorporated for sensitive areas.

Order data

Order number	Product description
LN-B2M	H.264 mechanical Day/Night-bullet camera, 3 mm - 10 mm, Dual Stream, 1/4" CMOS, 12VDC, PoE

GanzLite IP-Bulletcamera



Advantages for the installer

Although the cameras feature a wide range of options, their setup and configuration is straightforward. The clearly designed user menu provides full user support.

Technical specifications	LN-B2M
Sensor	1/4" CMOS
Compressionsformat	H.264 / MJPEG
Max. Resolution	2048 x 1536
Resolution options	h.264: 2048 x 1536 / 1600 x 1200 / 1920 x 1080 / 1280 x 720 MJPEG: 1280 x 960 / 1920 x 1080 / 1280 x 720
Effective pixel	2048 x 1536
Video framerate	h.264: 22fps @ 2048 x 1536 / 30fps @ 1920 x 1080 MJPEG: 15fps @ 1920 x 1080
Lens	3mm - 10mm F1.6
Iris control	Auto
S/N ratio	37dB
Alarm in/-output	1/1
Audio in/-output	1/1
Audiocodec	G.711 64kbps / G.726 32kbps
Day/night switching	Mechanical
Minimum illumination (F1.6/AGC)	0.1lux / 0lux (IR on)
Infrared	Yes, up to 15m / 30°
AGC/WDR/DNR	Yes/Yes/Yes
Network interface	RJ-45
Protocols	RTSP/RTP/UDP,RTSP/RTP/TCP,RTSP/RTP/HTTP tunneling, LAN Multicast, Multipart-JPEG IPv4, IPv6, HTTP, UDP, TCP, ICMP, IGMP, ARP, DHCP, NTP, SMTP, FTP, SAMBA, UPnP, PPPoE, DNS, DDNS, RTSP, RTP, RTCP,ONVIF
Security	Password protection / IP-Filter
Private zone masking	Yes
Alarm event	Object detection/Tamper/Power loss/Network failure/Motion detection/System start
Remote access	IE 6.0+ / iOS / Android / BlackBerry
Micro SD-card	Yes, up to 32GB
Motion detection	Yes
Power source	12VDC
PoE	Yes (IEEE802.3af)
Protection class	IP66
Power consumption	6W (IR on) / 4W
Operating environment	-20°C - 50°C
Dimensions (Ø x H)	65mm x 180mm
Weight	625g