



LN-D2M-IR

## The performance features at a glance

- H.264 & MJPEG
- 3.0 Megapixel
- Mechanical Day-/Nightswitching
- 3mm - 10mm Vario lens
- Indoor- and outdoormodels with IR-LEDs
- Dualstream
- Videoanalytics



LN-DT2M-IR

## High versatility

One dome is available for outside and another for indoor use. In this context both domes have integrated IR LEDs and can therefore be used in locations which are either poorly lit or not lit at all.

## Outstanding advantages

With a resolution of up to 2048 x 1536 both domes provide high quality and detailed images. In this context it is possible to show up to 22 images per second. In the full HD resolution the total is 30.

## High-performance technology

The three axis mechanism and the integrated 3mm – 10mm lens provide optimum visibility. The outdoor dome camera also features safety classes IP 68 and IK10 and is therefore optimally protected.

## Other special features

The integrated video analysis enables an even more detailed surveillance and control of the surrounding areas and its scope therefore extends beyond the integrated movement sensor feature. A privacy mask function is also incorporated for sensitive areas.

## Order data

Order number	Product description
LN-D2M-IR indoor LN-DT2M-IR outdoor	H.264 mechanical Day/Night-Domecamera, 3 mm - 10 mm, Dual Stream, 1/4" CMOS, 12VDC, PoE

# GanzLite IP-DOMECAMERA



## Advantages for the installer

Although the cameras feature a wide range of options, their setup and configuration is straightforward. The clearly designed user menu provides full user support.

Technical specifications	LN-D2M-IR	LN-DT2M-IR
Sensor	1/4" CMOS	
Compressionsformat	H.264 / MJPEG	
Max. Resolution	2048 x 1536	
Resolution options	h.264: 2048 x 1536 / 1600 x 1200 / 1920 x 1080 / 1280 x 720 MJPEG: 1280 x 960 / 1920 x 1080 / 1280 x 720	
Effective pixel	2048 x 1536	
Video framerate	h.264: 22fps @ 2048 x 1536 / 30fps @ 1920 x 1080 MJPEG: 15fps @ 1920 x 1080	
Lens	3mm - 10mm F1.6	
Iris control	Auto	
S/N ratio	37dB	
Alarm in-/output	1/1	
Audio in-/output	1/1	
Audiocodec	G.711 64kbps / G.726 32kbps	
Day/night switching	Mechanical	
Minimum illumination (F1.6/AGC)	0.1lux / 0lux (IR on)	
Infrared	Yes, up to 15m / 30°	Yes, up to 15m / 25°
AGC/WDR/DNR	Yes/Yes/Yes	
Network interface	RJ-45	
Protocols	RTSP/RTP/UDP, RTSP/RTP/TCP, RTSP/RTP/HTTP tunneling, LAN Multicast, Multipart-JPEG IPv4, IPv6, HTTP, UDP, TCP, ICMP, IGMP, ARP, DHCP, NTP, SMTP, FTP, SAMBA, UPnP, PPPoE, DNS, DDNS, RTSP, RTP, RTCP, ONVIF	
Security	Password protection / IP-Filter	
Private zone masking	Yes	
Alarm event	Object detection/Tamper/Power loss/Network failure/Motion detection/System start	
Remote access	IE 6.0+ / iOS / Android / BlackBerry	
Micro SD-card	Yes, up to 32GB	
Motion detection	Yes	
Power source	12VDC	
PoE	Yes (IEEE802.3af)	
Protection class	-	IP68
Power consumption	6.6W (IR on) / 4.8W	7.8W (IR on) / 4.2W
Operating environment	-10°C - 50°C	-20°C - 50°C
Dimensions (Ø x H)	130mm x 100.5mm	144.3mm x 115mm
Housing	-	IK10
Weight	874g	880g