



The performance features at a glance

- H.264 & MJPEG
- 2.0 Megapixel
- 3.6mm fix lens
- Dualstream
- Videoanalytics

High versatility

The indoor camera in a pleasing and simple design is able to monitor a vast area thanks to the 3.6 mm lens. Due to the high resolution, also more distant details are perfectly visible.

Outstanding advantages

With a resolution of up to 1600 x 1200 both domes provide high quality and detailed images. In this context it is possible to show up to 15 images per second. In the 1280 x 720-resolution the total is 30.

High-performance technology

Various access via network or Internet provide a comprehensive control option. As you quite like with Internet Explorer or via Smartphone.

Other special features

The integrated video analysis enables an even more detailed surveillance and control of the surrounding areas and its scope therefore extends beyond the integrated movement sensor feature. A privacy mask function is also incorporated for sensitive areas.

Order data

Order number	Product description
LN-MD136M	H.264 Minidome, 3.6mm, Dual Stream, 1/3" CMOS, 12VDC, PoE

GanzLite IP-Minidomecamera



Advantages for the installer

Although the cameras feature a wide range of options, their setup and configuration is straightforward. The clearly designed user menu provides full user support.

Technical specifications	LN-MD136M
Sensor	1/3" CMOS
Compressionsformat	H.264 / MJPEG
Max. Resolution	1600 x 1200
Resolution options	h.264: 1600 x 1200 / 1280 x 720 MJPEG: 1600 x 1200 / 1280 x 720
Effective pixel	1600 x 1200
Video framerate	h.264: 15bps @ 1600 x 1200 / 30bps @ 1280 x 720 MJPEG: 15bps @ 1600 x 1200 / 15bps @ 1280 x 720
Lens	3.6mm F1.8
Iris control	Auto
S/N ratio	42.3dB
Audio	Mic-In
Audiocodec	G.711 64kbps / G.726 32kbps
Day/Nightswitching	Electronical
Minimum illumination (F1.8/AGC)	0.1lux
AGC/DNR/BLC	Yes/Yes/Yes
Network interface	RJ-45
Protocols	RTSP/RTP/UDP,RTSP/RTP/TCP,RTSP/RTP/HTTP tunneling, LAN Multicast, Multipart-JPEG IPv4, IPv6, HTTP, UDP, TCP, ICMP, IGMP, ARP, DHCP, NTP, SMTP, FTP, SAMBA, UPnP, PPPoE, DNS, DDNS, RTSP, RTP, RTCP,ONVIF
Security	Password protection / IP-Filter
Private zone masking	Yes
Alarm event	Object detection/Tamper/Power loss/Network failure/Motion detection/System start
Remote access	IE 6.0+ / iOS / Android / BlackBerry
Motion detection	Yes
Power source	12VDC
PoE	Yes (IEEE802.3af)
Power consumption	3W
Operating environment	-10°C - 50°C
Dimensions (Ø x H)	107.1mm x 49.7mm
Weight	212g