

OPA4ED28IR

4MP HD IR Eyeball Dome

KEY FEATURES

- 4 megapixel True Day Night
- IP67 - Internal and external installations
- Integrated IR illumination - low light conditions
- Fixed lens - wide angle
- Quad video format - CVI/TVI/AHD/CVBS



Features		OPA4ED28IR Feature Specification
Camera	Image Sensor	1/2.7" CMOS
	Effective Pixels	2560(H)x1440(V)
	Electronic Shutter Speed	PAL: 1/25~1/100000 NTSC: 1/30~1/100000s
	Minimum Illumination	0.03Lux/F2.0, 30IRE, 0Lux IR on
	IR Distance	Up to 30m (98 feet)
Lens	Focal Length	2.8mm
	Max. Aperture	F2.0
	Angle of View	H: 76.4° (97.0°/48.6°) V: 41.6° (52°/27.9°)
Video	Resolution	4MP (2560x1440)
	Frame Rate	25/30fps@4MP, 25/30fps@1080P
	BLC Mode	BLC/HLC/DWDR
Certifications	Certifications	CE (EN55032, EN55024, EN50130-4)
Electrical	Power Supply	12VDC ±30%
	Power Consumption	Max 3.7W (12VDC, IR on)
Environmental	Operating Conditions	-40°C ~ +60°C (-40°F ~ +140°F)
	Storage Conditions	-40°C ~ +60°C (-40°F ~ +140°F)
	Ingress Protection	IP67
	Vandal Resistant	N/A
Construction	Casing	Aluminium
	Dimensions	Φ93.4mm×79.4mm (Φ3.68"×3.13")
	Net Weight	0.28kg (0.62lb)
	Gross Weight	0.38kg (0.84lb)

ORDERING INFORMATION

0000000 OPA4ED28IR

Associated brackets:

0486040	OPJB3	Junction box 3	0486120	OPPNPL	Pendant mount drop pole (Required for OPPNMA)
0486080	OPWB2	Wall bracket 2	0486920	OPSPMA	Side pole mount adaptor (Requires OPJB3)
0486110	OPPNMA	Pendant mount adaptor			