

OPI2VD28IR

2MP HD IR Vandal Dome

KEY FEATURES

- 2 Megapixel True Day/Night
- IP67 - Internal and external installations
- Integrated IR illumination - low light conditions
- Fixed lens - wide angle
- H.265 smart codec - efficient compression (reduced network traffic)



Features		OPI2VD28IR Feature Specification
Camera	Image Sensor	1/2.7" 2Megapixel progressive CMOS
	Effective Pixels	1920(H)x1080(V)
	Electronic Shutter Speed	Auto/Manual, 1/3-1/100000s
	Minimum Illumination	0.3Lux/F2.0(colour, 1/25s) 0Lux/F2.0(IR on)
	IR Distance	Distance up to 30m (98ft)
Lens	Focal Length	2.8mm
	Max. Aperture	F2.0
	Angle of View	H:104°, V:55°
Video	Resolution	1080P(1920x1080)/1.3M(1280x960) / 720P(1280x720)/D1(704x576/704x480) VGA(640x480) / CIF(352x288/352x240)
	Frame Rate	Main Stream: 1080P (1 - 25/30fps) Sub Stream: D1 (1 - 25/30fps)
	BLC Mode	BLC/HLC/DWDR
Network	Interoperability	ONVIF Profile S&G, API
	Smart Phone	iOS, Android
Certifications	Certifications	CE (EN 60950:2000)
Electrical	Power Supply	DC12V, PoE (802.3af)(Class 0)
	Power Consumption	<5.5W
Environmental	Operating Conditions	-30°C-60°C(-22°F-140°F)
	Storage Conditions	-30°C-60°C(-22°F-140°F)
	Ingress Protection	IP67
	Vandal Resistant	IK10
Construction	Casing	Metal
	Dimensions	Φ109.9mm × 81mm (4.33" × 3.19")
	Net Weight	0.34Kg (0.75lb)
	Gross Weight	0.47Kg (1.04lb)

ORDERING INFORMATION

0000000 OPI2VD28IR

Associated brackets:

0486060 OPJB5 Junction box 5
 0486070 OPWB1 Wall bracket 1
 0486090 OPCL1 Ceiling adaptor
 0486100 OPRS1 Rainsield

0486110 OPPNMA Pendant mount adaptor
(Requires OPPNPL)
 0486120 OPPNPL Pendant mount drop pole
 0486920 OPSPMA Side pole mount adaptor
(Requires OPJB4)