

OPI4ED28IR

4MP IP HD IR Eyeball Dome

KEY FEATURES

- 4 Megapixel True Day/Night
- IP67 – outside installations
- Integrated IR illumination – low light conditions
- Fixed lens – wide angle
- H.265 smart codec – efficient compression (reduced network traffic)



Features		OPI4ED28IR Feature Specification
Camera	Image Sensor	1/3" 4 Megapixel progressive CMOS
	Effective Pixels	2560(H)x1440(V)
	Electronic Shutter Speed	Auto/Manual, 1/3~1/100000s
	Minimum Illumination	0.5Lux/F2.0 (Colour, 1/25s) 0Lux/F2.0 (Mono IR on)
	IR Distance	Distance up to 30m (98ft)
Lens	Focal Length	2.8mm
	Max. Aperture	F2.0
	Angle of View	H:101°/V:54°
Video	Resolution	4MP (2560x1440)/3MP (2304x1296)/1080P (1920x1080)/720P (1280x720)/VGA (640x480)/D1 (704x576/704x480)/CIF (352x288/352x240)
	Frame Rate	Main Stream: 4M (1~20fps) Sub Stream: D1 (1~20fps)
	BLC Mode	BLC/HLC/DWDR
Network	Smart Phone	iOS, Android
Certifications	Certifications	CE: (EN 60950:2000)
Electrical	Power Supply	DC12V, PoE (802.3af) (Class 0)
	Power Consumption	<4.8W
Environmental	Operating Conditions	-30°C~60°C (-22°F~140°F)
	Storage Conditions	-30°C~60°C (-22°F~140°F)
	Ingress Protection	IP67
Construction	Casing	Metal
	Dimensions	Φ108mmx84.9mm (4.25"x3.34")
	Net Weight	0.26Kg (0.57lb)
	Gross Weight	0.39Kg (0.86lb)

ORDERING INFORMATION

0485900 OPI4ED28IR

Associated brackets:

0486040 OPJB3	Junction box 3	0486110 OPPNMA	Pendant mount adaptor (Requires OPPNPL)
0486080 OPWB2	Wall bracket 2	0486120 OPPNPL	Pendant mount drop pole (Requires OPWB2)
0486920 OPSPMA	Side pole mount adaptor		