

# OPI4VD28IR

## 4MP HD IR Vandal Dome

### KEY FEATURES

- 4 Megapixel True Day/Night
- IP67 - Internal and external installations
- Integrated IR illumination - low light conditions
- Fixed lens - wide angle
- H.265 smart codec - efficient compression (reduced network traffic)



Features		OPI4VD28IR Feature Specification
Camera	Image Sensor	1/3" 4 Megapixel progressive CMOS
	Effective Pixels	2560(H)x1440(V)
	Electronic Shutter Speed	Auto/Manual, 1/3~1/100000s
	Minimum Illumination	0.5Lux/F2.0 (Colour, 1/25s) 0Lux/F2.0 (Mono IR on)
	IR Distance	Distance up to 30m (98ft)
Lens	Focal Length	2.8mm
	Max. Aperture	F2.0
	Angle of View	H:101°/V:54°
Video	Resolution	4MP (2560x1440)/3MP (2304x1296)/1080P (1920x1080)/720P (1280x720) VGA (640x480)/D1 (704x576/704x480)/CIF (352x288/352x240)
	Frame Rate	Main Stream: 4M (1~20fps) Sub Stream: D1 (1~20fps)
	BLC Mode	BLC/HLC/DWDR
Network	Interoperability	ONVIF Profile S&G, API
	Smart Phone	iOS, Android
Certifications	Certifications	CE: (EN 60950:2000)
Electrical	Power Supply	12VDC, PoE (802.3af) (Class 0)
	Power Consumption	<3.9W
Environmental	Operating Conditions	-30°C~60°C (-22°F~140°F)
	Storage Conditions	-30°C~60°C (-22°F~140°F)
	Ingress Protection	IP67
	Vandal Resistant	IK10
Construction	Casing	Metal
	Dimensions	Φ122mmx98.1mm (4.8"x3.86")
	Net Weight	0.35Kg (0.77lb)
	Gross Weight	0.49Kg (1.08lb)

### ORDERING INFORMATION

0485920 OPI4VD28IR

#### Associated brackets:

0486050	OPJB4	Junction box 4	0486110	OPPNMA	Pendant mount adaptor (Requires OPPNPL)
0486070	OPWB1	Wall bracket 1	0486120	OPPNPL	Pendant mount drop pole
0486090	OPCL1	Ceiling adaptor	0486920	OPSPMA	Side pole mount adaptor (Requires OPJB4)
0486100	OPRS1	Rainsheild			