



## PROFESSIONAL HOUSING SOLUTION FOR GENERAL APPLICATIONS

The side opening VHE-23 external housings provide total access to the camera mounting platform for ease of installation. Each housing is also supplied with a fully cable-managed bracket and Infra-Red (IR) lamp-fixing points to eliminate any loose and unsightly cabling.

The housing is an ideal size to fit any CCTV camera with either a fixed or varifocal lens and with 3 fixing points on the underside, is useful for those sites that require additional light fittings such as IR illumination. The IP66 weatherproof housing not only looks smart and professional, but also reduces any vandal-related threats.

Clever features such as the inclusion of three separate cable glands ensure that the installer can separate each cable entry, benefiting from a perfect seal for each cable.

To learn more about this product range please visit us at [vista-cctv.com](http://vista-cctv.com)



### Key Features:

#### Side opening housing

The housing opens fully at the side to give free access to the camera and all connections for quick and easy installation and servicing

#### IP66 rated housing

This high rating ensures that the housing is dust tight and protected against high pressure jets of water

#### Flat base

The flat, open plan base provides total access to all internal connections. The camera mounting platform is also raised to assist with lens focusing

#### Three separate cable glands

Having three separate glands allows the installer to split the connecting cables between the glands, thus ensuring a perfect seal for each cable

#### Fully cable-managed bracket

This provides maximum protection for all cables entering the housing, increasing the integrity of the housing and providing a more professional installation

**FLEXIBILITY BY DESIGN**

## MODEL NUMBERS IN THIS RANGE:

**0356960** VHE-23HV IP66 fully cable managed housing & bracket, 240V AC  
**0356970** VHE-23LV IP66 fully cable managed housing & bracket, 24V  
**0442920** VHE-23-PB Pole bracket

## TECHNICAL SPECIFICATION:

|                       | VHE-23LV   | VHE23-HV  |
|-----------------------|--|---|
| Opening               | Side hinge with dual locking points via allen bolt   |   |
| Cable management      | 3 entry points with cable glands   |   |
| Fixing points         | 4 holes for wall fixing on bracket   |   |
| Internal connections  | Fused, pre-wired terminal block (Camera, heater & illumination)  |   |
| External connections  | 3no 1/4" UNC fixing points for illumination device / module  |   |
| Mounting              | Wall mount or Pole (via additional bracketry)  |   |
| Material              | Aluminium  |   |
| Colour                | RAL7035  |   |
| Dimensions            | 403(L) x 129(W) x 128(H) mm (net)<br>260(L) x 90(W) x 85(H) mm (MCL)<br>160 (H) x 445 (W) x 260 (D) mm (gross) |   |
| Weight                | 3.7Kg  |   |
| Operating temperature | -10° to +50°C  |   |
| Thermostat            | Heater on @ 15°C, off @ 25°C   |   |
| IP Rating             | IP66   |   |
| Power                 | 14W / 580mA @ 24VAC  | 22W / 90mA @ 240VAC (running)<br>288W / 1.2A @ 240VAC (initial surge) |



No liability will be accepted by Vista for any errors or omissions in this information.  
Subject to change without notice.

VHE-23 - Version6