

Fully cable managed bracket

The VVRD-EWMB1 is a fully cable managed wall bracket for use both internally and externally with VVRD style cameras.

The low profile design incorporates a void above the camera mounting to ensure that cables don't have to be aggressively angled and allows the connections and any excess cable to be concealed.

A 3/4" NPT thread on the front of the housing allows the bracket to interface with conduit and a small removable plate allows connections to be made and tested in-situ without the need to remove the camera.

Constructed of aluminium and powder coated, it allows this bracket to be suitable for both external and internal applications with both Vista analogue and IP VVRD style cameras.

Will fit:

VVRD580 series
VVRD650
VVRDE700 series
VPL6-WP-SM
VK2-VRD
VK2-2MPVRD
VK2-600PTZ
Eclipse²



Key Features:

Fully cable managed

The low profile design allows connections to be made and kept within the bracket along with any excess cable.

Conduit connection

The 3/4" NPT port on the front of the bracket allows multiple cable entry points.

Cable access plate

Allows cables to be easily accessible for maintenance, without having to disturb the camera.

Multiple camera compatibility

The 4 bolt, Ø121mm PCD ensures that the following (but not limited to) Vista 'dome' style cameras will fit: VVRD580, VVRD650, VVRDE700, VPL6-WP-SM, VK2-VRD, VK2-2MPVRD, VK2-600PTZ, Eclipse² (coming soon)

Robust construction

The die cast aluminium construction and RAL7035 powder coating ensures this bracket is suitable for both internal and external applications.

MODEL NUMBER:

0479030 VVRD-EWMB1 VVRD/VPL6 wall bracket

TECHNICAL SPECIFICATION:

Model	VVRD-EWMB1
Construction	Die cast aluminium
Colour	RAL7035
Maximum load	11lbs / 5.0Kgs
Inlet Dimensions	¾" NPT
Camera mounting PCD	4 bolt pattern, Ø121mm PCD
Dimensions (net)	170 (W) x 230 (L) x 146 (H)
Dimensions (gross)	180 (W) x 245 (H) x 150 (D)
Weight (net)	1090g
Weight (gross)	1320g