

# WIP2PTZ20IR

## 2MP IP PTZ Speed Dome



WIP2PTZ20IR

### Key Features

- 1/3" 2MP CMOS Progressive Scan
- HD Network Video Output : 1920 x 1080P@25/30fps
- 4.7 ~ 94mm, 20 x 200m Lens
- SD Card Local Storage / Snapshot Images
- Network Remote Storage
- Web GUI Menu for Engineer Setup
- CVBS Video Output
- 1x Audio Input, 1x Audio Output
- 7 NO/NC Alarm Inputs / 1 Alarm Output
- 100m IR Illumination (In Ideal Conditions)

## Technical Specification

Model Number	WIP2PTZ20IR
Image Sensor	1/3" Progressive CMOS
Image Pixels	1920 x 1080
Minimum Illumination	0 Lux
IR Distance	100m
WB	Auto/Manual
S/N Ratio	>50dB
Day/Night	Auto/Manual/Timing
Focus Mode	Auto/Manual
Lens	20x Zoom, f=4.7 ~ 94mm, F1.6 ~ F3.5
Pan Range	360 Endless Rotation
Pan Speed	Preset Speed: 240° /S: Manual Control Speed: 0.5 ~ 90°/S
Tilt Range	0 ~ 90° (Auto Rotation)
Tilt Speed	Preset Speed: 240°/S: Manual Control Speed: 0.5~90°/S
PTZ Control	Support
Preset	255
Patrol	8
Pan	4
Time Task	8
Scan	2
Home Position Display	Support
Auto Flip	Support
Alarm Input	7Ch (NC/NO)
Alarm Output	1CH
Compression	H.264
Frame Rate	1 ~ 30fps (25fps)
Protocol	TCP/IP, UDP, DHCP, DDNS, NTP, RTSP, SMTP, FTP, PPPoE
Storage	SD Card Local Storage, Network Remote Storage, Still Images
Smart Alarm	Motion ,Sensor
Resolution	1920 x 1080, 1280 x 720, 640 x 480, 320 x 240, 160 x 120
Multi-Stream	Support
Network Interface	10Base-T/100Base-TX,RJ45
Audio	Mic Input x1, Mic Output x1
Analogue Output	CVBS
Control	RS485/Network
Power Supply	AC24V/3000mA
Power Consumption	15w (Max.65W,IR ON Heater ON)
Working Environment	Temperature: -20°C ~ 60°C, Humidity: Less than 95%
IP Rating	IP66
Dimensions (Ø x H)	Ø216 x 349 mm
Weight	5kg

Features and specifications are subject to change for further improvement without any notice

www.geniecctv.com  
 sales@geniecctv.com  
 T: +44 (0) 1707 330 541  
 F: +44 (0) 1707 330 543

Genie CCTV Ltd.  
 CCTV House, City Park,  
 Watchmead,  
 Welwyn Garden City,  
 Hertfordshire,  
 AL7 1LT,  
 United Kingdom