



WNVR14P5

H.265 4 Channel High Definition PoE NVR

The WNVR14P5 is a H.265 4 Channel High Definition Network Video Recorder. The NVR features 4 Channel Simultaneous Playback as well as 4 PoE Network Ports with IPC Direct Connection to NVR.



WNVR14P FRONT



WNVR14P BACK

Key Features

- Up to 5MP Real Time Recording across all 4 Channels
- H.265 Video Compression
- Supports 4 IP Stream Input
- Supports up to 4 PoE Power Supply
- 4 Channel Simultaneous Playback
- Supports 4K Output
- 1 HDD Bay (Up to 6TB)
- Multi-Mode Recording: Manual, Sensor (Via the Alarm Inputs of the IP Camera), Schedule and Motion
- Multi-User Online Simultaneously
- Support PTZ Presets
- Pentaplex: Live, Record, Playback, Backup and Remote Operation
- DHCP, DDNS, PPPoE, Network Protocol, IE Browse and CMS Supported
- Support IPC Direct Connection to NVR
- Dual Stream Technology to Encode Recording Stream and Network Stream
- User can adjust Network Stream to fit Bandwidth without changing Recording Quality
- User Friendly Graphic User Interface (GUI), Windows Style, Operation By Mouse
- Apple & Android Mobile Phone Remote Viewing

Technical Specification

| | |
|--------------------------|--|
| Model Number | WNVR14P5 |
| Compression | Standard H.265 |
| OS | Embedded Linux |
| IP Video Input | 4 Channels |
| Network Access Bandwidth | 40 Mbps |
| Video Output | HDMI: x1: 4K x 2K / 1920 x 1080/1280 x 1024 VGA: 1920 x 1080/ 1280 x 1024 |
| Record Resolution | 5MP/4MP/3MP/1080P/960P/720P |
| Frame Rate | 1~25fps / CH (PAL), 1~30fps / CH (NTSC) |
| Audio | Output: RCA x1, 2 Way Audio: RCA x1 |
| Record Stream | Dual Stream Recording |
| Recording Mode | Manual, Timer, Motion, Sensor |
| Playback | Max 4ch Simultaneous |
| Search | Time slice/time/event/tag search |
| Alarm Mode | Time/Calendar Search, Event (Motion, External Alarm) |
| Function | Play, Pause, FF, FB, Digital Zoom |
| Network Interface | RJ45 x1 (10/100 Mbps x1) |
| PoE Port | RJ45 x4 |
| Network Interface | RJ45 x1 |
| Protocol | TCP/IP, UDP, DHCP, DNS, PPPOE, DDNS |
| Web Client | Up to 10 Users Online |
| Mobile OS | iPhone, Blackberry, Android, Windows Phone |
| Mobile Function | Multi-Screen Surveillance (for certain model), Record, Snapshot, PTZ Control, Save the Device list |
| Ports | RS485: x1 (Support PTZ) USB 2.0: x2 Ports |
| Remote Controller | Yes |
| Power Supply | DC48V |
| Working Environment | 10 ~ 55°C, 10% ~ 90% Humidity |
| Dimensions (W x D x H) | 300 x 270 x 55 mm |

Genie CCTV reserves the right to change specifications without notice. Please contact your representative to confirm current specifications.

Dimensions (mm)

