



WNVR8 Series

3MP High Resolution IP NVR's



WNVR8 Series

Key Features

- 16 and 32 Channels
- User Friendly Graphic User Interface (GUI), Windows Style, Operation By Mouse
- Remote Control via IE or CMS: Preview, Playback, Backup, PTZ and Configuration
- Multi-Mode Recording: Manual, Sensor, Schedule and Motion
- 16 Channel Playback
- Search: Time/Calendar, Events (Alarm, Motion)
- Flexible Backup via USB, Network or DVD-RW (Sata)
- Pentaplex: Live, Record, Playback, Backup and Remote Operation
- DHCP, DDNS, PPPoE, Network Protocol, IE Browse and CMS Supported
- Dual Stream Technology to Encode Recording Stream and Network Stream. User can adjust Network Stream to fit Bandwidth without changing Recording quality.
- Multi-User Online Simultaneously
- HDMI 1080P Output
- Support PTZ Preset and Auto Cruise, Up to 128 Presets and 8 Cruises
- Complete SDK Function, easy to integrate with other applications

DATASHEET

www.geniecctv.com
sales@geniecctv.com
T: +44 (0) 1707 330 541
F: +44 (0) 1707 330 543

Genie CCTV Ltd.
CCTV House, City Park,
Watchmead,
Welwyn Garden City,
Hertfordshire,
AL7 1LT,
United Kingdom

Technical Specification

Model Number	WNVR816	WNVR832
Compression	Standard H.264	
CPU	Cortex A9 Dual Core	
OS	Embedded Linux	
Video Output	BNC: x 1, VGA: x1 1080P (1920 x 1080), HDMI: x1 (1920 x 1080)	
IP Input	1080P: 8CH@30fps, 16CH@15fps 720P: 16CH@30fps D1: 16CH@30fps	3MP: 32CH@30fps 1080P: 32CH@30fps, 720P: 16CH@30fps D1: 16CH@30fps
Audio	Output: RCA x1, 2 Way Audio: RCA x1	Input: 32CH IPC, Output: RCA x1, 2 Way Audio: RCA x1
Record Resolution	1080P / 720P / D1	3MP: (2048 x 1536) 1080P: (1920 x 1080) 960P: (1280 x 960) 720P: (1280 x 960) D1: (704 x 576)
Frame Rate	1~25fps / CH (PAL), 1~30fps / CH (NTSC)	800fps (PAL), 960fps (NTSC)
Bit Rate	2M ~ 12Mbps	256Kbps ~ 12Mbps
Encode	VBR/CBR	
Quality	6 Level	
Recording Mode	Manual, Timer, Motion, Sensor	
File Manager	Lock, Unlock, Reversing Time	
Playback	16CH	16CH
Search	Time/Calendar Search, Event (Motion, External Alarm)	
Smart Search	Apply different colours to display whether a channel in a period of time recording or not	
Function	Play, Pause, FF, FB, Digital Zoom	
Alarm Mode	Sensor, Motion, Video Loss	
Alarm Input	16CH	
Alarm Output	4CH	
Triggering	Record, PTZ Move, Alarm Out, E-mail, etc	
Network Interface	RJ45 x1	GMAC x1
Protocol	TCP/IP, UDP, DHCP, DNS, PPPOE, DDNS, E-mail	
Others	10 Users Online, Dual Stream	18 Users Online, Dual Stream
Mobile OS	iPhone, Android	
Mobile Function	Multi-Screen Surveillance (for certain model), Record, Snapshot, PTZ Control, Save the Device list	
Ports	HDD: Sata x8 RS485: x2, Support PTZ and Keyboard USB: USB3.0 x1, USB2.0 x 1	
Remote Controller	Yes	
Power Supply	AC110V / AC220V	AC110V / AC240V
Working Environment	0 ~ 50°C, 10% ~ 90% Humidity	10 ~ 50°C, 10% ~ 90% Humidity
Dimensions (W x D x H)	430 x 450 x 89 mm	

Features and specifications are subject to change for further improvement without any notice

Dimensions (mm)

