

The WNVR8645 is a 64 channel high definition 8MP network video recorder with 8 HDD bays. The WNVR8645 features up to 16 channel simultaneous playback as well as 2 10/100/1000 network ports which supports dual LAN network configuration. The NVR can support the latest H.265 and H.264 encoding streams. The WNVR8645 NVR has a dedicated iPhone and Android App (Super Live Plus) and are supplied with free Windows / MAC CMS software.



WNVR8645 Front





WNVR8645 Back

## Key Features

- Support 64 channel 8MP, 5MP, 4MP, 3MP, 1080P, 960P and 720P IP input
- H.265 high profile compression format for high quality video at much lower bit rate
- Intuitive and user friendly Graphic User Interface (GUI), Windows style operation by mouse
- Multi-mode recording: Manual, Timer, Motion, Sensor
- Playback : 16 channel simultaneous playback
- Search : Time slice, Time, Event (Manual, sensor, motion), Tag search
- Pentaplex : Preview, Record, Playback, Backup and Remote access
- DHCP, DDNS, PPPoE network protocol and CMS supported
- Remote control via IE or CMS : Preview, Playback, Backup, PTZ and Configuration
- Express and flexible backup via USB, network and so on
- Immix platform is supported - running firmware 1.1.0 or later
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Authorisation management, log view and device status view
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QR Code scanning by mobile phone and iPad
- Powerful smart phone & iPad surveillance with iOS and Android OS
- 4K output, high resolution display
- Multi-user online simultaneously

## Dimensions (mm)





## Specification

<b>Model Number</b>	WNVR8645
<b>Compression</b>	Standard H.265 High Profile
<b>System OS</b>	Embedded Linux
<b>Video Network Input</b>	64 channel IPC input
<b>Network Access Bandwidth</b>	320 Mbps
<b>Network Access Format</b>	8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P @ 25/30fps
<b>Video Output</b>	HDMI x 1: 4K x 2K / 1920 x 1080 / 1280 x 1024, HDMI x 1: 1920 x 1080 / 1280 x 1024 VGA x 1: 1920 x 1080 / 1280 x 1024
<b>Audio Network Input</b>	64 channel IPC audio input
<b>Two Way Audio</b>	RCA x 1
<b>Audio Local Output</b>	RCA x 1
<b>Record Stream</b>	Dual stream recording
<b>Record Resolution</b>	8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P
<b>Record Mode</b>	Manual, Timer, Motion, Sensor
<b>Simultaneous Playback</b>	Max. 16 channel
<b>Smart Search</b>	Highlighted colour to display the camera record in a certain period of time, different colours refer to different record events.
<b>Function</b>	Play, Pause, FF, FB, Digital Zoom, etc.
<b>Search</b>	Time slice / Time / Event / Tag search
<b>Alarm Mode</b>	Manual, Sensor, Motion, Exception
<b>Alarm Input</b>	8 channel local alarm input, support channel IPC alarm input
<b>Alarm Output</b>	4 channel
<b>Alarm Triggering</b>	Record, Snap, Preset, E-Mail, etc.
<b>Network Interface</b>	RJ45 10 / 100 / 1000 Mbps x 2
<b>PoE Port</b>	No
<b>Network Protocol</b>	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP
<b>Web Client</b>	Max. 10 users online
<b>Mobile OS</b>	iOS, Android
<b>Immix Support</b>	Yes, Firmware 1.1.0 or later
<b>Storage</b>	HDD: SATA x 8, e-SATA x 2, Max. 10TB per HDD
<b>Backup</b>	Local: U Disk, USB mobile HDD, Network: Yes
<b>USB</b>	USB 2.0 x 1 , USB 3.0 x 1 (One in the front panel and the other in the rear panel)
<b>Remote Control</b>	Yes
<b>Power Supply</b>	ATX
<b>Power Consumption</b>	≤15W (Without HDD)
<b>Environment Conditions</b>	-10°C ~ 50°C, 10%-90% Humidity
<b>Dimensions</b>	430 (W) x 453 (L) x 89 (H) mm

Bioaccess Sales Ltd. reserves the right to change specifications without notice. Please contact your representative to confirm current specifications.