



Installation Devices / Installation Devices: Interface,
Relay,Activ,Acc/Call

Product Code

F02013

ADDITIONAL FUNCTIONS RELAY

Reference	EAN
2013	8424299020136

Description.

Description

Small size allows installation in electrical cabinets. Can be flush-fit in standard boxes 10x10 cm. With adhesive strips for fixing, or may be screwed directly onto the wall. Necessary to activate an external device (courtesy light, second door, etc) from the corresponding button (additional button) located in the phone or monitor.

Technical Details

Maximum operation/second: 20
Power supply: Terminals "+18V" y "3" = +18 Vdc
Terminals "3" and "4" = 8 Vdc
Consumption: Standby: 0 mA - Active: 70 mA
Operating temperature: -30°C +65 °C, HR 90% without condensation
Dimensions: 61.3 x 68.6 x 20.4 mm (ALxANxProf)
Contacts: Maximum commutable voltage: 220 Vac (1 A) 36 Vac (2 A)

Dimensions: 62x70x20 mm (height-width-depth).

Details.

Weight (kg)	Dimensions (cm)	Video Door Entry system
0.05508	6,3x2,4x9	Technologie
		GENERICA

Manuals

94457c_Rele_2013_V07_08.pdf

Declaration of conformity

DOCF02013EN.pdf